



Section 1. Identification

Product name :	Jotafloor PU Universal Comp A
Code :	12320
Product description :	Paint.
Product type :	Liquid.
Other means of : identification	Not available.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Professional spray painting, near-industrial setting Professional low-energy painting, near-industrial setting Professional spray painting, indoor (Level II) Professional painting, indoor brush/roller Professional spray painting, outdoor (Level II) Professional painting, outdoor brush/roller

Supplier	: Jotun Australia Pty. Ltd. 59 Calarco Drive, Derrimut, VIC 3026, Australia
	Phone: + 61 39314 0722 E-mail: SDSJotun@jotun.com
Emergency telephone number	: Medical Emergencies 24 hours: Poisons Information Centre (Australia) 131 126

JOTUN

Jotun Protects Property

Section 2. Hazard(s) identification

Classification of the substance or mixture	: SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category	2
GHS label elements		
Hazard pictograms	:	
Signal word	: WARNING	
Hazard statements	: H373 - May cause damage to organs through prolonged or repeated expos (lungs)	sure.
Precautionary statements		
Prevention	: P260 - Do not breathe vapour or spray.	
Response	: P314 - Get medical advice/attention if you feel unwell.	
Storage	: Not applicable.	

Section 2. Hazard(s) identification

Disposal	: P501 - Dispose of contents and container in accordance with all local, reginational and international regulations.	onal,
Supplemental label elements	: Not applicable.	
Other hazards which do not result in classification	: None known.	

Section 3. Composition and ingredient information

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

CAS number	: Not applicable.		
EC number	: Mixture.		
Product code	: 12320		
Ingredient name		% (w/w)	CAS number
silica, crystalline - quartz		≤10	14808-60-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary fire	st aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Date of issue/Date of revision	: 15.06.2023	Date of previous issue	:16.11.2022	Version : 1.08	2/10
--------------------------------	--------------	------------------------	-------------	----------------	------

Section 4. First aid measures

Potential acute health effe	<u>ets</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.
Unsuitable extinguishing media	: Do not use water jet.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Evacu enteri mist.	tion shall be taken involving an iate surrounding areas. Keep ng. Do not touch or walk throu Provide adequate ventilation. quate. Put on appropriate per	unnecessary and unp ugh spilt material. Avo Wear appropriate res	rotected perso bid breathing v pirator when v	onnel fro apour o	r
For emergency responders	inform	cialised clothing is required to nation in Section 8 on suitable nation in "For non-emergency	and unsuitable materi			
Date of issue/Date of revision	15.06.2023	Date of previous issue	: 16.11.2022	Version	: 1.08	3/10

Section 6. Accidental release measures

Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for cor	ntai	nment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

See Technical Data Sheet / packaging for further information.

Section 8. Exposure controls and personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Control parameters

Occupational exposure limits

silica, crystalline - quartz

Safe Work Australia (Australia, 12/2019). TWA: 0.05 mg/m³ 8 hours. Form:

Respirable dust

Section 8. Exposure controls and personal protection

Appropriate engineering controls	: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.		
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measu	res		
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	: Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		
Skin protection			
 Hand protection Chemical-resistant, impervious gloves complying with an approved stand be worn at all times when handling chemical products if a risk assessment this is necessary. Considering the parameters specified by the glove many check during use that the gloves are still retaining their protective propert should be noted that the time to breakthrough for any glove material may different for different glove manufacturers. In the case of mixtures, consistent several substances, the protection time of the gloves cannot be accurated estimated. There is no one glove material or combination of materials that will give up the several substances. 			
	resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.		
	Gloves should be replaced regularly and if there is any sign of damage to the glove		
	material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical		
	damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.		
	Wear suitable gloves tested to ISO 374-1:2016. Recommended, gloves(breakthrough time) > 8 hours: butyl rubber (> 0.4 mm), PVC (> 0.5 mm), nitrile rubber (> 0.4 mm), neoprene (> 0.35 mm) May be used, gloves(breakthrough time) 4 - 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm)		
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. 		
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.		

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Blue., Grey
Odour	: Characteristic.
Odour threshold	: Not applicable.
рН	: Not applicable.
Melting point	: Not applicable.
Boiling point	: Lowest known value: 313°C (595.4°F) (castor oil).
Flash point	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not applicable.
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 1.488 to 1.506 g/ cm ³
Solubility	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

Section 10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingre	edients.
Chemical stability	The product is stable.	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not oc	cur.
Conditions to avoid	No specific data.	
Incompatible materials	Keep away from the following materials to prevent strong exothermic reactio oxidising agents, strong alkalis, strong acids.	ons:
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition prod should not be produced.	lucts

Section 11. Toxicological information

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
silica, crystalline - quartz	Category 2	inhalation	lungs

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effect	cts as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Section 11. Toxicological information

<u>Long term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	

Potential chronic health effects

Not available.

General	: May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soilSoil/water partition
coefficient (Koc): Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

 Disposal methods
 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 13. Disposal considerations

Do not allow to enter drains or watercourses. Material and/or container must be disposed of as hazardous waste.

Section 14 Transport information

	ADG	ADR/RID	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

This preparation is not classified as dangerous according to international transport regulations (ADR/RID, IMDG or ICAO/IATA).

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

Ingredient name	<u>Schedule</u>
silica, crystalline - quartz silica, crystalline - quartz	Restricted hazardous chemical Restricted hazardous chemical [For abrasive blasting at a concentration of greater than 1%]

Australia inventory (AIIC) : Not determined.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Section 15. Regulatory information

UNECE Aarhus Protocol on POPs and Heavy Metals Not listed.

Section 16. Any other relevant information

<u>History</u>	
Date of printing	: 15.06.2023
Date of issue/Date of revision	: 15.06.2023
Date of previous issue	: 16.11.2022
Version	: 1.08
Key to abbreviations	 ADG = Australian Dangerous Goods ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOHSC = National Occupational Health and Safety Commission SUSMP = Standard for the Uniform Scheduling of Medicines and Poisons UN = United Nations

Procedure used to derive the classification

Classification	Justification
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2	Calculation method

References

: Not available.

✓ Indicates information that has changed from previously issued version.

<u>Disclaimer</u>

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.