

# SAFETY DATA SHEET



## Hardtop Smart Pack Comp A

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Hardtop Smart Pack Comp A  
**Product code** : 18940  
**Product description** : Paint.  
**Product type** : Liquid.  
**Other means of identification** : Not available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use

#### 1.3 Details of the supplier of the safety data sheet

Jotun A/S  
P.O. Box 2021  
3202 Sandefjord Norway

Tel: + 47 33 45 70 00  
Fax: +47 33 45 72 42  
sdsjotun@jotun.no

#### National contact

Jotun Italia S.r.l.  
Via Oliviero Petronio, 8  
34015 Muggia (TS)  
Italy

Tel: +39 040 23 98 111/23 98 203  
Fax: +39 040 4606968  
SDSJotun@jotun.com  
info@jotun.it

#### 1.4 Emergency telephone number

CAV "Ospedale Pediatrico Bambino Gesù" – Roma - Tel. (+39) 06.6859.3726  
CAV "Azienda Ospedaliera Università di Foggia" – Foggia - Tel. 800.183.459  
CAV "Azienda Ospedaliera A. Cardarelli" – Napoli - Tel. (+39) 081.545.3333  
CAV Policlinico "Umberto I" – Roma - Tel. (+39) 06.4997.8000  
CAV Policlinico "A. Gemelli" – Roma - Tel. (+39) 06.305.4343  
CAV Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica – Firenze - Tel. (+39) 055.794.7819  
CAV Centro Nazionale di Informazione Tossicologica – Pavia - Tel. (+39) 0382.24.444  
CAV Ospedale Niguarda – Milano - Tel. (+39) 02.66.1010.29  
CAV Azienda Ospedaliera Papa Giovanni XXIII – Bergamo - Tel. 800.88.33.00  
CAV Centro Antiveneni Veneto – Verona - Tel. 800.011.858

Hardtop Smart Pack Comp A

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT SE 3, H335

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning.

**Hazard statements** : H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H411 - Toxic to aquatic life with long lasting effects.

#### Precautionary statements

**General** : Not applicable.

**Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapour.

**Response** : P391 - Collect spillage.  
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 - Keep cool.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : xylene  
epoxy resin (MW 700-1200)  
hydrocarbons, C9, aromatics  
butan-1-ol  
decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester, mixt. with  
1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidiny) decanedioate  
fatty acids, C14-18 and C16-18-unsatd., maleated  
maleic anhydride

**Supplemental label elements** : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed.  
Do not breathe spray or mist.

Hardtop Smart Pack Comp A

**SECTION 2: Hazards identification**

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

**2.3 Other hazards**

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
epoxy resin (MW 700-1200)	CAS: 25036-25-3	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
hydrocarbons, C9, aromatics	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	≤10	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	-	[1]
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4	≤5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
ethylbenzene	REACH #:	≤5	Flam. Liq. 2, H225	ATE [Inhalation	[1] [2]

## Hardtop Smart Pack Comp A

## SECTION 3: Composition/information on ingredients

	01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4		Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	(vapours)] = 11 mg/l	
butan-1-ol	REACH #: 01-2119484630-38 EC: 200-751-6 CAS: 71-36-3 Index: 603-004-00-6	≤2.9	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	ATE [Oral] = 500 mg/kg	[1]
decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester, mixt. with 1-methyl 10- (1,2,2,6,6-pentamethyl-4-piperidinyl) decanedioate	REACH #: 01-2119491304-40 CAS: 1065336-91-5	<3	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
fatty acids, C14-18 and C16-18-unsatd., maleated	REACH #: 01-2119976378-19 EC: 288-306-2 CAS: 85711-46-2	<1	Skin Irrit. 2, H315 Skin Sens. 1, H317	-	[1]
maleic anhydride	REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9	≤0.1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) STOT RE 2, H373 EUH071 <b>See Section 16 for the full text of the H statements declared above.</b>	ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001%	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

## Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

## 4.1 Description of first aid measures

## General

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

## Eye contact

: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

## Inhalation

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

## SECTION 4: First aid measures

- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

- 6.3 Methods and material for containment and cleaning up** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

#### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Seveso Directive - Reporting thresholds

Hardtop Smart Pack Comp A

**SECTION 7: Handling and storage**Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c E2	5000 tonne 200 tonne	50000 tonne 500 tonne

See Technical Data Sheet / packaging for further information.

**7.3 Specific end use(s)****Recommendations** : Not available.**Industrial sector specific solutions** : Not available.**SECTION 8: Exposure controls/personal protection**

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters**Occupational exposure limits

Product/ingredient name	Exposure limit values
xylene	<b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).</b> <b>[Xilene, isomeri misti, puro] Absorbed through skin.</b> Short Term: 442 mg/m <sup>3</sup> 15 minutes. Short Term: 100 ppm 15 minutes. Limit value: 221 mg/m <sup>3</sup> 8 hours. Limit value: 50 ppm 8 hours.
n-butyl acetate	<b>EU OEL (Europe, 1/2022). Notes:</b> STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes. TWA: 241 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
ethylbenzene	<b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).</b> <b>Absorbed through skin.</b> Limit value: 100 ppm 8 hours. Limit value: 442 mg/m <sup>3</sup> 8 hours. Short Term: 200 ppm 15 minutes. Short Term: 884 mg/m <sup>3</sup> 15 minutes.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs



**SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Type	Exposure	Value	Population	Effects
xylene	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic
trizinc bis(orthophosphate)	DNEL	Long term Inhalation	5 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	83 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Oral	0.83 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	12.5 mg/kg bw/day	Workers	Systemic
hydrocarbons, C9, aromatics	DNEL	Long term Inhalation	151 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	7.5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	32 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Oral	7.5 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	0.41 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	1.9 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	178.57 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	640 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	837.5 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	1066.67 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term	1152 mg/	General	Systemic



## Hardtop Smart Pack Comp A

**SECTION 8: Exposure controls/personal protection**

n-butyl acetate	DNEL	Inhalation Short term	m <sup>3</sup> 1286.4 mg/m <sup>3</sup>	population Workers	Systemic
	DNEL	Inhalation Short term	960 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Short term	960 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Long term	480 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Inhalation Long term	480 mg/m <sup>3</sup>	Workers	Local
	DNEL	Inhalation Short term	859.7 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Inhalation Short term	859.7 mg/m <sup>3</sup>	General population [Consumers]	Local
	DNEL	Inhalation Long term	102.34 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Inhalation Long term	102.34 mg/m <sup>3</sup>	General population [Consumers]	Local
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	48 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic
ethylbenzene	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic
	DMEL	Long term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DMEL	Short term Inhalation	884 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	15 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic

## Hardtop Smart Pack Comp A

**SECTION 8: Exposure controls/personal protection**

butan-1-ol	DNEL	Short term Inhalation	293 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	1.5625 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	55.357 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	155 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	310 mg/m <sup>3</sup>	Workers	Local
decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidiny) ester, mixt. with 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidiny) decanedioate	DNEL	Long term Oral	0.18 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.31 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	0.9 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.27 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	1.8 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
fatty acids, C14-18 and C16-18-unsatd., maleated	DNEL	Long term Dermal	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.05 mg/m <sup>3</sup>	General population	Systemic
maleic anhydride	DNEL	Long term Inhalation	0.06 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.08 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.081 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	0.081 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Oral	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0.2 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	0.2 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	0.2 mg/m <sup>3</sup>	Workers	Systemic

**PNECs**

**SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Compartment Detail	Value	Method Detail
xylene	Fresh water	0.327 mg/l	-
	Marine	0.327 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Fresh water sediment	12.46 mg/kg dwt	-
	Marine water sediment	12.46 mg/kg dwt	-
trizinc bis(orthophosphate)	Soil	2.31 mg/kg dwt	-
	Fresh water	20.6 µg/l	-
	Marine	6.1 µg/l	-
	Sewage Treatment Plant	52 µg/l	-
	Fresh water sediment	117.8 mg/kg dwt	-
n-butyl acetate	Marine water sediment	56.5 mg/kg dwt	-
	Soil	35.6 mg/kg dwt	-
	Fresh water	0.18 mg/l	-
	Marine	0.018 mg/l	-
	Sewage Treatment Plant	35.6 mg/l	-
ethylbenzene	Fresh water sediment	0.981 mg/kg dwt	-
	Marine water sediment	0.0981 mg/kg dwt	-
	Soil	0.0903 mg/kg dwt	-
	Fresh water	0.1 mg/l	-
	Marine	0.01 mg/l	-
butan-1-ol	Sewage Treatment Plant	9.6 mg/l	-
	Fresh water sediment	13.7 mg/kg dwt	-
	Soil	2.68 mg/kg dwt	-
	Secondary Poisoning	20 mg/kg	-
	Fresh water	0.082 mg/l	-
	Marine	0.0082 mg/l	-
	Sewage Treatment Plant	2476 mg/l	-
	Fresh water sediment	0.178 mg/kg dwt	-
	Marine water sediment	0.0178 mg/kg dwt	-
	Soil	0.015 mg/kg dwt	-

**8.2 Exposure controls****Appropriate engineering controls**

- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

**Individual protection measures****Hygiene measures**

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection**

- : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection****Hand protection**

## SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

### Gloves

Wear suitable gloves tested to ISO 374-1:2016.

Not recommended, gloves(breakthrough time) < 1 hour: butyl rubber (> 0.4 mm)

May be used, gloves(breakthrough time) 4 - 8 hours: Viton® (> 0.7 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm)

Recommended, gloves(breakthrough time) > 8 hours: fluor rubber (> 0.35 mm), nitrile rubber (> 0.75 mm), 4H/ Silver Shield® (> 0.07 mm), Teflon (> 0.35 mm), polyvinyl alcohol (PVA) (> 0.3 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- |  |  |
|--|--|
| <b>Body protection</b>                 | : Use chemical-resistant protective suit / disposable overall.<br>Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.  |
| <b>Other skin protection</b>           | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |
| <b>Respiratory protection</b>          | : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter. |
| <b>Environmental exposure controls</b> | : Do not allow to enter drains or watercourses.  |

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- |  |   |
|--|---|
| <b>Physical state</b>                          | : Liquid.   |
| <b>Colour</b>                                  | : Black, Green., Grey, MCI Base 1, MCI Base 2, MCI Base 3, MCI Base 5, MCI Base 6, Orange, Red, White., Yellow. |
| <b>Odour</b>                                   | : Characteristic.   |
| <b>Odour threshold</b>                         | : Not applicable.   |
| <b>Melting point/freezing point</b>            | : Not available.  |
| <b>Initial boiling point and boiling range</b> | : Lowest known value: 119°C (246.2°F) (butan-1-ol). Weighted average: 141.75°C (287.1°F)                        |
| <b>Flammability</b>                            | : Not applicable.   |
| <b>Lower and upper explosion limit</b>         | : Greatest known range: Lower: 1.4% Upper: 11.3% (butan-1-ol)   |
| <b>Flash point</b>                             | : Closed cup: 28°C  |
| <b>Auto-ignition temperature</b>               | : Lowest known value: 280 to 470°C (536 to 878°F) (hydrocarbons, C9, aromatics).                                |

**Hardtop Smart Pack Comp A****SECTION 9: Physical and chemical properties**

<b>Decomposition temperature</b>	: Not available.
<b>pH</b>	: Not applicable.
<b>Viscosity</b>	: Kinematic (40°C): >20.5 mm <sup>2</sup> /s
<b>Solubility in water</b>	: cold water      Not soluble hot water      Not soluble
<b>Partition coefficient: n-octanol/ water</b>	: Not available.
<b>Vapour pressure</b>	: Highest known value: 1.5 kPa (11.3 mm Hg) (at 20°C) (n-butyl acetate). Weighted average: 0.89 kPa (6.68 mm Hg) (at 20°C)
<b>Evaporation rate</b>	: Highest known value: 1 (n-butyl acetate) Weighted average: 0.8 compared with butyl acetate
<b>Density</b>	: 1.33 to 1.52 g/cm <sup>3</sup>
<b>Vapour density</b>	: Highest known value: 4 (Air = 1) (n-butyl acetate). Weighted average: 3.66 (Air = 1)
<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.
<b>Particle characteristics</b>	
<b>Median particle size</b>	: Not applicable.

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
xylylene	LC50 Inhalation Vapour	Rat	11 mg/l	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
	TDLo Dermal	Rabbit	4300 mg/kg	-
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	13100 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat - Male	11 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
butan-1-ol	LD50 Oral	Rat	790 mg/kg	-
maleic anhydride	LD50 Oral	Rat	400 mg/kg	-

**Acute toxicity estimates**

**Hardtop Smart Pack Comp A****SECTION 11: Toxicological information**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Hardtop Smart Pack Comp A	27777.8	9214.1	N/A	69.0	N/A
xylene	4300	1100	N/A	11	N/A
n-butyl acetate	13100	N/A	N/A	N/A	N/A
ethylbenzene	3500	N/A	N/A	11	N/A
butan-1-ol	500	N/A	N/A	N/A	N/A
maleic anhydride	400	N/A	N/A	N/A	N/A

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Eyes - Mild irritant Skin - Mild irritant	Rabbit Rat	- -	87 milligrams 8 hours 60 microliters	- -
epoxy resin (MW 700-1200)	Eyes - Mild irritant  Skin - Mild irritant	Mammal - species unspecified Mammal - species unspecified	- -	- -	- -
fatty acids, C14-18 and C16-18-unsatd., maleated	Skin - Mild irritant	Mammal - species unspecified	-	-	-
maleic anhydride	Eyes - Severe irritant	Rabbit	-	1 Percent	-

**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
epoxy resin (MW 700-1200)	skin	Mammal - species unspecified	Sensitising
fatty acids, C14-18 and C16-18-unsatd., maleated	skin	Mammal - species unspecified	Sensitising
maleic anhydride	skin	Mammal - species unspecified	Sensitising

**Mutagenicity**

No known significant effects or critical hazards.

**Carcinogenicity**

No known significant effects or critical hazards.

**Reproductive toxicity****Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.**Teratogenicity**

No known significant effects or critical hazards.

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
hydrocarbons, C9, aromatics	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects
butan-1-ol	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation

**Hardtop Smart Pack Comp A****SECTION 11: Toxicological information**

	Category 3		Narcotic effects
--	------------	--	------------------

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene maleic anhydride	Category 2 Category 1 Category 2	- inhalation	hearing organs respiratory system

**Aspiration hazard**

Product/ingredient name	Result
xylene hydrocarbons, C9, aromatics ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

**11.2 Information on other hazards****11.2.1 Endocrine disrupting properties**

Not available.

**11.2.2 Other information**

Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
xylene	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
trizinc bis(orthophosphate)	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 0.14 mg/l	Fish - Oncorhynchus mykiss	96 hours
hydrocarbons, C9, aromatics	Chronic NOEC 0.1 mg/l	Micro-organism	4 hours
	Acute EC50 <10 mg/l	Daphnia	48 hours
	Acute IC50 <10 mg/l	Algae	72 hours
ethylbenzene	Acute LC50 <10 mg/l	Fish	96 hours
	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 2.93 mg/l	Daphnia	48 hours
	Acute LC50 4.2 mg/l	Fish	96 hours
decanedioic acid, 1,10-bis (1,2,2,6,6-pentamethyl-4-piperidinyl) ester, mixt. with 1-methyl 10- (1,2,2,6,6-pentamethyl-4-piperidinyl) decanedioate	Acute EC50 1.68 mg/l	Algae	96 hours
	Acute LC50 0.9 mg/l	Fish	96 hours
	Chronic NOEC 1 mg/l	Daphnia	21 days
maleic anhydride	Acute LC50 230 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours

**Conclusion/Summary** : Water polluting material. May be harmful to the environment if released in large quantities. This material is toxic to aquatic life with long lasting effects.

**12.2 Persistence and degradability**

**Conclusion/Summary** : Not available.



Hardtop Smart Pack Comp A

**SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
xylene	-	-	Readily
trizinc bis(orthophosphate)	-	-	Not readily
hydrocarbons, C9, aromatics	-	-	Not readily
ethylbenzene	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
xylene	3.12	8.1 to 25.9	low
trizinc bis(orthophosphate)	-	60960	high
hydrocarbons, C9, aromatics	-	10 to 2500	high
n-butyl acetate	2.3	-	low
ethylbenzene	3.6	-	low
butan-1-ol	1	-	low
maleic anhydride	-2.78	-	low

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Endocrine disrupting properties**

Not available.

**12.7 Other adverse effects**

No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**European waste catalogue (EWC)**

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Hardtop Smart Pack Comp A

**SECTION 13: Disposal considerations**

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

**Packaging**








**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	UN1263	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	Paint	Paint	Paint. Marine pollutant (trizinc bis (orthophosphate))	Paint
<b>14.3 Transport hazard class(es)</b>	3  	3  	3  	3 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

**Additional information****ADR/RID**

: **Hazard identification number** 30  
**Viscous liquid exception** This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.  
**Tunnel code** (D/E)

**ADN**

: **Viscous liquid exception** This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.2.3.1.5.2.

Hardtop Smart Pack Comp A

## SECTION 14: Transport information

- IMDG** : **Emergency schedules** F-E, S-E  
**Viscous liquid exception** This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.
- UN** : **Viscous liquid exception** This class 3 viscous liquid that is also environmentally hazardous is not subject to regulation in packagings up to 5 L, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 according to 2.3.2.5.2.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : Not available.

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

*Hardtop Smart Pack Comp A***SECTION 15: Regulatory information**

Not listed.

**Seveso Directive**

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

**National regulations**

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**D.Lgs. 152/06** : Not determined.

**International regulations****Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**15.2 Chemical safety assessment** : Not applicable.

**SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**


: ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**


Classification	Justification
Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

**Full text of abbreviated H statements**

**Hardtop Smart Pack Comp A****SECTION 16: Other information**

	H225	Highly flammable liquid and vapour.
	H226	Flammable liquid and vapour.
	H302	Harmful if swallowed.
	H304	May be fatal if swallowed and enters airways.
	H312	Harmful in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H332	Harmful if inhaled.
	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H335	May cause respiratory irritation.
	H336	May cause drowsiness or dizziness.
	H361f	Suspected of damaging fertility.
	H372	Causes damage to organs through prolonged or repeated exposure.
	H373	May cause damage to organs through prolonged or repeated exposure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	H412	Harmful to aquatic life with long lasting effects.
	EUH066	Repeated exposure may cause skin dryness or cracking.
	EUH071	Corrosive to the respiratory tract.

**Full text of classifications [CLP/GHS]**

	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
	Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
	Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
	Repr. 2	REPRODUCTIVE TOXICITY - Category 2
	Resp. Sens. 1	RESPIRATORY SENSITISATION - Category 1
	Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
	Skin Sens. 1	SKIN SENSITISATION - Category 1
	Skin Sens. 1A	SKIN SENSITISATION - Category 1A
	STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
	STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
	STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of printing** : 22.07.2025**Date of issue/ Date of revision** : 22.07.2025**Date of previous issue** : 22.03.2023**Version** : 2**Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.