

## Resist 65 Comp A

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : Resist 65 Comp A  
**UFI** : D30S-51EX-U00F-0M3T  
**Product code** : 19860  
**Product description** : Paint.  
**Product type** : Liquid.  
**Other means of identification** : Not available.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Professional use

#### 1.3 Details of the supplier of the safety data sheet

Jotun A/S  
P.O.Box 2021  
3202 Sandefjord  
Norway  
Tel: + 47 33 45 70 00  
Fax: +47 33 45 72 42  
E-mail: SDSJotun@jotun.no

Jotun Paints (Europe) Ltd.  
Stather Road  
Flixborough, Scunthorpe  
North Lincolnshire  
DN15 8RR  
England

Tel: +44 17 24 40 00 00  
Fax: +44 17 24 40 01 00

#### 1.4 Emergency telephone number

##### National advisory body/Poison Centre

**Telephone number** : Contact NHS Direct; phone 0845 4647 or 111. Open 24/7.

##### Supplier

**Telephone number** : +47 33 45 70 00 Jotun Norway (head office)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to UK CLP/GHS

Flam. Liq. 2, H225  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger.

Resist 65 Comp A

## SECTION 2: Hazards identification

- Hazard statements** : H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H412 - Harmful to aquatic life with long lasting effects.
- Precautionary statements**
- General** : Not applicable.
- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.
- Response** : P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P302 + P352 - IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : Not applicable.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Not applicable.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
- Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers   | %         | Classification  | Type    |
|-------------------------|---|-----------|---|---------|
| ethanol                 | REACH #:<br>01-2119457610-43<br>EC: 200-578-6<br>CAS: 64-17-5<br>Index: 603-002-00-5  | ≥10 - ≤25 | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319  | [1] [2] |
| kaolin                  | EC: 310-127-6<br>CAS: 1332-58-7   | ≥10 - ≤25 | Not classified.   | [2]     |
| mica                    | EC: 310-127-6<br>CAS: 12001-26-2  | ≥10 - ≤25 | Not classified.   | [2]     |
| 2-butoxyethanol         | REACH #:<br>01-2119475108-36<br>EC: 203-905-0<br>CAS: 111-76-2<br>Index: 603-014-00-0 | ≤10       | Acute Tox. 4, H302<br>Acute Tox. 3, H331<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319 | [1] [2] |

Resist 65 Comp A

**SECTION 3: Composition/information on ingredients**

|                      |  |      |   |         |
|----------------------|--|------|---|---------|
| tetraethyl silicate  | REACH #:<br>01-2119496195-28<br>EC: 201-083-8<br>CAS: 78-10-4<br>Index: 014-005-00-0   | ≤5   | Flam. Liq. 3, H226<br>Acute Tox. 4, H332<br>Eye Irrit. 2, H319<br>STOT SE 3, H335   | [1] [2] |
| xylene               | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br>CAS: 1330-20-7<br>Index: 601-022-00-9 | ≤5   | Flam. Liq. 3, H226<br>Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3,<br>H412   | [1] [2] |
| 1-methoxy-2-propanol | REACH #:<br>01-2119457435-35<br>EC: 203-539-1<br>CAS: 107-98-2<br>Index: 603-064-00-3  | ≤5   | Flam. Liq. 3, H226<br>STOT SE 3, H336   | [1] [2] |
| ethylbenzene         | REACH #:<br>01-2119489370-35<br>EC: 202-849-4<br>CAS: 100-41-4<br>Index: 601-023-00-4  | ≤2.2 | Flam. Liq. 2, H225<br>Acute Tox. 4, H332<br>STOT RE 2, H373<br>(hearing organs)<br>Asp. Tox. 1, H304<br>Aquatic Chronic 3,<br>H412  | [1] [2] |
| zinc chloride        | EC: 231-592-0<br>CAS: 7646-85-7<br>Index: 030-003-00-2                                 | <1   | Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>STOT SE 3, H335<br>Aquatic Acute 1, H400<br>(M=1)<br>Aquatic Chronic 1,<br>H410 (M=1)<br><b>See Section 16 for<br/>the full text of the H<br/>statements declared<br/>above.</b> | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures****Eye contact**

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation**

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact**

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**SECTION 4: First aid measures**

- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**4.2 Most important symptoms and effects, both acute and delayed**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Over-exposure signs/symptoms**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

## SECTION 5: Firefighting measures

**Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| P5c      | 5000 tonne                      | 50000 tonne             |

See Technical Data Sheet / packaging for further information.

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

| Product/ingredient name | Exposure limit values  |
|-------------------------|--|
| ethanol                 | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 1920 mg/m <sup>3</sup> 8 hours.   |
| kaolin                  | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 1000 ppm 8 hours.   |
| mica                    | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable dust  |
| 2-butoxyethanol         | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 0.8 mg/m <sup>3</sup> 8 hours. Form: respirable<br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: total inhalable<br><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>STEL: 50 ppm 15 minutes.<br>TWA: 25 ppm 8 hours.<br>STEL: 246 mg/m <sup>3</sup> 15 minutes. |

Resist 65 Comp A

## SECTION 8: Exposure controls/personal protection

|                      |   |
|----------------------|---|
| tetraethyl silicate  | TWA: 123 mg/m <sup>3</sup> 8 hours.<br><b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b>   |
| xylene               | TWA: 44 mg/m <sup>3</sup> 8 hours.<br>TWA: 5 ppm 8 hours.<br><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>STEL: 441 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |
| 1-methoxy-2-propanol | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>STEL: 560 mg/m <sup>3</sup> 15 minutes.<br>STEL: 150 ppm 15 minutes.<br>TWA: 375 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours.   |
| ethylbenzene         | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b><br>STEL: 552 mg/m <sup>3</sup> 15 minutes.<br>STEL: 125 ppm 15 minutes.<br>TWA: 100 ppm 8 hours.<br>TWA: 441 mg/m <sup>3</sup> 8 hours.   |
| zinc chloride        | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>STEL: 2 mg/m <sup>3</sup> 15 minutes. Form: Fume<br>TWA: 1 mg/m <sup>3</sup> 8 hours. Form: Fume  |

### Biological exposure indices

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

| Product/ingredient name | Type | Exposure              | Value                  | Population                     | Effects  |
|-------------------------|------|-----------------------|------------------------|--------------------------------|----------|
| ethanol                 | DNEL | Long term Oral        | 87 mg/kg bw/day        | General population             | Systemic |
|                         | DNEL | Long term Inhalation  | 114 mg/m <sup>3</sup>  | General population             | Systemic |
|                         | DNEL | Long term Dermal      | 206 mg/kg bw/day       | General population             | Systemic |
|                         | DNEL | Long term Dermal      | 343 mg/kg bw/day       | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 950 mg/m <sup>3</sup>  | General population             | Local    |
|                         | DNEL | Long term Inhalation  | 950 mg/m <sup>3</sup>  | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 1900 mg/m <sup>3</sup> | Workers                        | Local    |
| 2-butoxyethanol         | DNEL | Short term Dermal     | 89 mg/kg bw/day        | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 663 mg/m <sup>3</sup>  | Workers                        | Systemic |
|                         | DNEL | Short term Inhalation | 246 mg/m <sup>3</sup>  | Workers                        | Local    |
|                         | DNEL | Long term Dermal      | 75 mg/kg bw/day        | Workers                        | Systemic |
|                         | DNEL | Long term Inhalation  | 98 mg/m <sup>3</sup>   | Workers                        | Systemic |
|                         | DNEL | Short term Dermal     | 44.5 mg/kg bw/day      | General population [Consumers] | Systemic |
|                         | DNEL | Short term            | 426 mg/m <sup>3</sup>  | General                        | Systemic |

Resist 65 Comp A

**SECTION 8: Exposure controls/personal protection**

|                     |                   |                          |                            |                                      |          |
|---------------------|-------------------|--------------------------|----------------------------|--------------------------------------|----------|
| tetraethyl silicate |                   | Inhalation               |                            | population<br>[Consumers]            |          |
|                     | DNEL              | Short term Oral          | 13.4 mg/<br>kg bw/day      | Workers                              | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 123 mg/m <sup>3</sup>      | General<br>population<br>[Consumers] | Local    |
|                     | DNEL              | Long term Dermal         | 38 mg/kg<br>bw/day         | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 49 mg/m <sup>3</sup>       | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Long term Oral           | 3.2 mg/kg<br>bw/day        | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Long term Oral           | 6.3 mg/kg<br>bw/day        | General<br>population                | Systemic |
|                     | DNEL              | Short term Oral          | 26.7 mg/<br>kg bw/day      | General<br>population                | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 59 mg/m <sup>3</sup>       | General<br>population                | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 98 mg/m <sup>3</sup>       | Workers                              | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 147 mg/m <sup>3</sup>      | General<br>population                | Local    |
|                     | DNEL              | Short term<br>Inhalation | 246 mg/m <sup>3</sup>      | Workers                              | Local    |
|                     | DNEL              | Short term<br>Inhalation | 426 mg/m <sup>3</sup>      | General<br>population                | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 1091 mg/<br>m <sup>3</sup> | Workers                              | Systemic |
|                     | DNEL              | Short term Dermal        | 12.1 mg/<br>kg bw/day      | Workers                              | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 85 mg/m <sup>3</sup>       | Workers                              | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 85 mg/m <sup>3</sup>       | Workers                              | Local    |
|                     | DNEL              | Long term Dermal         | 12.1 mg/<br>kg bw/day      | Workers                              | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 85 mg/m <sup>3</sup>       | Workers                              | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 85 mg/m <sup>3</sup>       | Workers                              | Local    |
|                     | DNEL              | Short term Dermal        | 8.4 mg/kg<br>bw/day        | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 25 mg/m <sup>3</sup>       | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Short term<br>Inhalation | 25 mg/m <sup>3</sup>       | General<br>population<br>[Consumers] | Local    |
|                     | DNEL              | Long term Dermal         | 8.4 mg/kg<br>bw/day        | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 25 mg/m <sup>3</sup>       | General<br>population<br>[Consumers] | Systemic |
|                     | DNEL              | Long term<br>Inhalation  | 25 mg/m <sup>3</sup>       | General<br>population<br>[Consumers] | Local    |
| DNEL                | Short term Dermal | 3 mg/kg<br>bw/day        | General<br>population      | Systemic                             |          |



Resist 65 Comp A

**SECTION 8: Exposure controls/personal protection**

|              |                      |                       |                         |                       |                    |          |
|--------------|----------------------|-----------------------|-------------------------|-----------------------|--------------------|----------|
| xylene       | DNEL                 | Long term Dermal      | 3 mg/kg bw/day          | General population    | Systemic           |          |
|              | DNEL                 | Short term Inhalation | 14 mg/m <sup>3</sup>    | General population    | Local              |          |
|              | DNEL                 | Long term Inhalation  | 14 mg/m <sup>3</sup>    | General population    | Local              |          |
|              | DNEL                 | Short term Inhalation | 14 mg/m <sup>3</sup>    | General population    | Systemic           |          |
|              | DNEL                 | Long term Inhalation  | 14 mg/m <sup>3</sup>    | General population    | Systemic           |          |
|              | DNEL                 | Short term Dermal     | 56 mg/kg bw/day         | Workers               | Systemic           |          |
|              | DNEL                 | Long term Dermal      | 56 mg/kg bw/day         | Workers               | Systemic           |          |
|              | DNEL                 | Long term Inhalation  | 65.3 mg/m <sup>3</sup>  | General population    | Local              |          |
|              | DNEL                 | Short term Inhalation | 260 mg/m <sup>3</sup>   | General population    | Local              |          |
|              | DNEL                 | Short term Inhalation | 260 mg/m <sup>3</sup>   | General population    | Systemic           |          |
|              | DNEL                 | Long term Inhalation  | 221 mg/m <sup>3</sup>   | Workers               | Local              |          |
|              | DNEL                 | Long term Oral        | 12.5 mg/kg bw/day       | General population    | Systemic           |          |
|              | DNEL                 | Long term Inhalation  | 65.3 mg/m <sup>3</sup>  | General population    | Systemic           |          |
|              | DNEL                 | Long term Dermal      | 125 mg/kg bw/day        | General population    | Systemic           |          |
|              | DNEL                 | Long term Dermal      | 212 mg/kg bw/day        | Workers               | Systemic           |          |
|              | DNEL                 | Long term Inhalation  | 221 mg/m <sup>3</sup>   | Workers               | Systemic           |          |
|              | 1-methoxy-2-propanol | DNEL                  | Short term Inhalation   | 442 mg/m <sup>3</sup> | Workers            | Local    |
|              |                      | DNEL                  | Short term Inhalation   | 442 mg/m <sup>3</sup> | Workers            | Systemic |
| DNEL         |                      | Long term Oral        | 33 mg/kg bw/day         | General population    | Systemic           |          |
| DNEL         |                      | Long term Inhalation  | 43.9 mg/m <sup>3</sup>  | General population    | Systemic           |          |
| DNEL         |                      | Long term Dermal      | 78 mg/kg bw/day         | General population    | Systemic           |          |
| DNEL         |                      | Long term Dermal      | 183 mg/kg bw/day        | Workers               | Systemic           |          |
| DNEL         |                      | Long term Inhalation  | 369 mg/m <sup>3</sup>   | Workers               | Systemic           |          |
| DNEL         |                      | Short term Inhalation | 553.5 mg/m <sup>3</sup> | Workers               | Local              |          |
| DNEL         |                      | Short term Inhalation | 553.5 mg/m <sup>3</sup> | Workers               | Systemic           |          |
| ethylbenzene |                      | DNEL                  | Long term Oral          | 1.6 mg/kg bw/day      | General population | Systemic |
|              | DNEL                 | Long term Inhalation  | 15 mg/m <sup>3</sup>    | General population    | Systemic           |          |
|              | DNEL                 | Long term Inhalation  | 77 mg/m <sup>3</sup>    | Workers               | Systemic           |          |
|              | DNEL                 | Long term Dermal      | 180 mg/kg bw/day        | Workers               | Systemic           |          |
|              | DNEL                 | Short term Inhalation | 293 mg/m <sup>3</sup>   | Workers               | Local              |          |
|              | DMEL                 | Long term Inhalation  | 442 mg/m <sup>3</sup>   | Workers               | Local              |          |
|              | DMEL                 | Short term Inhalation | 884 mg/m <sup>3</sup>   | Workers               | Systemic           |          |

Resist 65 Comp A

## SECTION 8: Exposure controls/personal protection

|               |      |                      |                        |                    |          |
|---------------|------|----------------------|------------------------|--------------------|----------|
| zinc chloride | DNEL | Long term Inhalation | 1.25 mg/m <sup>3</sup> | General population | Systemic |
|               | DNEL | Long term Oral       | 0.83 mg/kg bw/day      | General population | Systemic |
|               | DNEL | Long term Inhalation | 1 mg/m <sup>3</sup>    | Workers            | Systemic |
|               | DNEL | Long term Dermal     | 8.3 mg/kg bw/day       | General population | Systemic |
|               | DNEL | Long term Dermal     | 8.3 mg/kg bw/day       | Workers            | Systemic |

### PNECs

| Product/ingredient name | Compartment Detail     | Value           | Method Detail |
|-------------------------|------------------------|-----------------|---------------|
| 2-butoxyethanol         | Fresh water            | 8.8 mg/l        | -             |
|                         | Marine                 | 0.88 mg/l       | -             |
|                         | Sewage Treatment Plant | 463 mg/l        | -             |
|                         | Fresh water sediment   | 34.6 mg/kg dwt  | -             |
|                         | Marine water sediment  | 3.46 mg/kg dwt  | -             |
|                         | Soil                   | 3.13 mg/kg dwt  | -             |
|                         | Secondary Poisoning    | 20 mg/kg        | -             |
| tetraethyl silicate     | Fresh water            | 0.19 mg/l       | -             |
|                         | Marine                 | 0.019 mg/l      | -             |
|                         | Sewage Treatment Plant | 4000 mg/l       | -             |
|                         | Fresh water sediment   | 0.83 mg/kg dwt  | -             |
|                         | Marine water sediment  | 0.083 mg/kg dwt | -             |
|                         | Soil                   | 0.05 mg/kg dwt  | -             |
|                         | Secondary Poisoning    | 20 mg/kg        | -             |
| xylene                  | Fresh water            | 0.327 mg/l      | -             |
|                         | Marine                 | 0.327 mg/l      | -             |
|                         | Sewage Treatment Plant | 6.58 mg/l       | -             |
|                         | Fresh water sediment   | 12.46 mg/kg dwt | -             |
|                         | Marine water sediment  | 12.46 mg/kg dwt | -             |
|                         | Soil                   | 2.31 mg/kg dwt  | -             |
|                         | Secondary Poisoning    | 20 mg/kg        | -             |
| 1-methoxy-2-propanol    | Fresh water            | 10 mg/l         | -             |
|                         | Marine                 | 1 mg/l          | -             |
|                         | Sewage Treatment Plant | 100 mg/l        | -             |
|                         | Fresh water sediment   | 52.3 mg/kg dwt  | -             |
|                         | Marine water sediment  | 5.2 mg/kg dwt   | -             |
|                         | Soil                   | 5.49 mg/kg dwt  | -             |
|                         | Secondary Poisoning    | 20 mg/kg        | -             |
| ethylbenzene            | Fresh water            | 0.1 mg/l        | -             |
|                         | Marine                 | 0.01 mg/l       | -             |
|                         | Sewage Treatment Plant | 9.6 mg/l        | -             |
|                         | Fresh water sediment   | 13.7 mg/kg dwt  | -             |
|                         | Soil                   | 2.68 mg/kg dwt  | -             |
|                         | Secondary Poisoning    | 20 mg/kg        | -             |

### 8.2 Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### Individual protection measures

**SECTION 8: Exposure controls/personal protection**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Skin protection****Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves**

Wear suitable gloves tested to ISO 374-1:2016.

Not recommended, gloves(breakthrough time) < 1 hour: PVC (> 0.5 mm)

Recommended, gloves(breakthrough time) > 8 hours: butyl rubber (> 0.4 mm), Viton® (> 0.7 mm), 4H/Silver Shield® (> 0.07 mm)

May be used, gloves(breakthrough time) 4 - 8 hours: neoprene (> 0.35 mm), Teflon (> 0.35 mm), nitrile rubber (> 0.4 mm), polyvinyl alcohol (PVA) (> 0.3 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoal filter.

**Environmental exposure controls** : Do not allow to enter drains or watercourses.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

**Physical state** : Liquid.

**Colour** : Grey

Resist 65 Comp A

**SECTION 9: Physical and chemical properties**

|   |   |
|---|---|
| <b>Odour</b>  | : Characteristic.   |
| <b>Odour threshold</b>                              | : Not applicable.   |
| <b>Melting point/freezing point</b>                 | : Not applicable.   |
| <b>Initial boiling point and boiling range</b>      | : Lowest known value: 78.29°C (172.9°F) (ethanol). Weighted average: 117.49°C (243.5°F) |
| <b>Flammability</b>                                 | : Not applicable.   |
| <b>Upper/lower flammability or explosive limits</b> | : 0.8 - 23%   |
| <b>Flash point</b>                                  | : Closed cup: 16°C (60.8°F)   |
| <b>Auto-ignition temperature</b>                    | : Lowest known value: 222°C (431.6°F) (tetraethyl silicate).                            |
| <b>Decomposition temperature</b>                    | : Not available.  |
| <b>pH</b>   | : Not applicable.   |
| <b>Viscosity</b>                                    | : Kinematic (40°C): >20.5 mm <sup>2</sup> /s  |
| <b>Solubility(ies)</b>                              | :   |

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |
| hot water  | Not soluble |

**Partition coefficient: n-octanol/ water** : Not available.

**Vapour pressure** : Highest known value: 5.7 kPa (43 mm Hg) (at 20°C) (ethanol). Weighted average: 2.89 kPa (21.68 mm Hg) (at 20°C)

**Evaporation rate** : Highest known value: 1.7 (ethanol) Weighted average: 1.05 compared with butyl acetate

**Density** : 1.34 g/cm<sup>3</sup>

**Vapour density** : Highest known value: 7.22 (Air = 1) (tetraethyl silicate). Weighted average: 3.17 (Air = 1)

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

**Particle characteristics**

**Median particle size** : Not applicable.

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Acute toxicity**

| Product/ingredient name | Result                  | Species                   | Dose                     | Exposure |
|-------------------------|-------------------------|---------------------------|--------------------------|----------|
| ethanol                 | LC50 Inhalation Vapour  | Rat                       | 124700 mg/m <sup>3</sup> | 4 hours  |
|                         | LD50 Oral               | Guinea pig - Male, Female | 1414 mg/kg               | -        |
| 2-butoxyethanol         | LD50 Oral               | Rat - Male, Female        | 1300 mg/kg               | -        |
|                         | LD50 Oral               | Rat - Male, Female        | 1300 mg/kg               | -        |
| xylene                  | LC50 Inhalation Vapour  | Rat                       | 20 mg/l                  | 4 hours  |
|                         | LD50 Oral               | Rat                       | 4300 mg/kg               | -        |
| 1-methoxy-2-propanol    | TDL <sub>o</sub> Dermal | Rabbit                    | 4300 mg/kg               | -        |
|                         | LD50 Dermal             | Rabbit                    | 13 g/kg                  | -        |
| ethylbenzene            | LD50 Oral               | Rat                       | 6600 mg/kg               | -        |
|                         | LC50 Inhalation Vapour  | Rat - Male                | 17.8 mg/l                | 4 hours  |
| zinc chloride           | LD50 Dermal             | Rabbit                    | >5000 mg/kg              | -        |
|                         | LD50 Oral               | Rat                       | 3500 mg/kg               | -        |
|                         | LD50 Oral               | Rat                       | 350 mg/kg                | -        |

**Acute toxicity estimates**

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|-------------------------|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| Resist 65 Comp A        | 15170.7      | 24733.0        | N/A                      | 29.8                        | N/A                                 |
| ethanol                 | 7000         | N/A            | N/A                      | 124.7                       | N/A                                 |
| 2-butoxyethanol         | 1200         | N/A            | N/A                      | 3                           | N/A                                 |
| tetraethyl silicate     | N/A          | N/A            | N/A                      | 11                          | N/A                                 |
| xylene                  | 4300         | 1100           | N/A                      | 20                          | N/A                                 |
| 1-methoxy-2-propanol    | 6600         | 13000          | N/A                      | N/A                         | N/A                                 |
| ethylbenzene            | 3500         | N/A            | N/A                      | 17.8                        | N/A                                 |
| zinc chloride           | 350          | N/A            | N/A                      | N/A                         | N/A                                 |

**Irritation/Corrosion**

| Product/ingredient name | Result                   | Species                      | Score | Exposure        | Observation |
|-------------------------|--------------------------|------------------------------|-------|-----------------|-------------|
| ethanol                 | Eyes - Moderate irritant | Rabbit                       | -     | 100 microliters | -           |
|                         | Skin - Mild irritant     | Rabbit                       | -     | 400 milligrams  | -           |
| 2-butoxyethanol         | Eyes - Moderate irritant | Rabbit                       | -     | 24 hours 100 mg | -           |
|                         | Skin - Mild irritant     | Rabbit                       | -     | 500 mg          | -           |
| tetraethyl silicate     | Eyes - Mild irritant     | Mammal - species unspecified | -     | -               | -           |
|                         | Eyes - Mild irritant     | Mammal - species unspecified | -     | -               | -           |

Resist 65 Comp A

## SECTION 11: Toxicological information

|                      |  |                  |        |  |        |
|----------------------|--|------------------|--------|--|--------|
| xylene               | Eyes - Mild irritant<br>Skin - Mild irritant   | Rabbit<br>Rat    | -<br>- | 87 milligrams<br>8 hours 60<br>microliters | -<br>- |
| 1-methoxy-2-propanol | Eyes - Mild irritant                           | Rabbit           | -      | 24 hours 500<br>mg                         | -      |
| zinc chloride        | Skin - Mild irritant<br>Skin - Severe irritant | Rabbit<br>Rabbit | -<br>- | 500 mg<br>120 hours 1<br>Percent           | -<br>- |

### Sensitisation

Based on available data, the classification criteria are not met.

### Mutagenicity

No known significant effects or critical hazards.

### Carcinogenicity

No known significant effects or critical hazards.

### Reproductive toxicity

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Teratogenicity

No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs                |
|-------------------------|------------|-------------------|------------------------------|
| tetraethyl silicate     | Category 3 | -                 | Respiratory tract irritation |
| xylene                  | Category 3 | -                 | Respiratory tract irritation |
| 1-methoxy-2-propanol    | Category 3 | -                 | Narcotic effects             |
| zinc chloride           | Category 3 | -                 | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category   | Route of exposure | Target organs  |
|-------------------------|------------|-------------------|----------------|
| ethylbenzene            | Category 2 | -                 | hearing organs |

### Aspiration hazard

| Product/ingredient name | Result                         |
|-------------------------|--------------------------------|
| xylene                  | ASPIRATION HAZARD - Category 1 |
| ethylbenzene            | ASPIRATION HAZARD - Category 1 |

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation.

**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : No specific data.

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness

**Ingestion** : No specific data.

Resist 65 Comp A

**SECTION 11: Toxicological information****General** : No known significant effects or critical hazards.**Other information** : None identified.**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

| Product/ingredient name | Result                            | Species   | Exposure |
|-------------------------|-----------------------------------|---|----------|
| 2-butoxyethanol         | Acute EC50 1000 mg/l Fresh water  | Daphnia - Water flea - Daphnia magna                        | 48 hours |
|                         | Acute LC50 1000 mg/l Marine water | Crustaceans - Amphipod - Chaetogammarus marinus - Young     | 48 hours |
| xylene                  | Acute LC50 8500 µg/l Marine water | Crustaceans - Daggerblade grass shrimp - Palaemonetes pugio | 48 hours |
|                         | Acute LC50 13400 µg/l Fresh water | Fish - Fathead minnow - Pimephales promelas                 | 96 hours |
| ethylbenzene            | Acute EC50 7700 µg/l Marine water | Algae - Diatom - Skeletonema costatum                       | 96 hours |
|                         | Acute EC50 2.93 mg/l              | Daphnia   | 48 hours |
|                         | Acute LC50 4.2 mg/l               | Fish  | 96 hours |

**Conclusion/Summary** : This material is harmful to aquatic life with long lasting effects.**12.2 Persistence and degradability****Conclusion/Summary** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |
| ethylbenzene            | -                 | -          | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------|--------------------|-------------|-----------|
| ethanol                 | -0.35              | -           | low       |
| 2-butoxyethanol         | 0.81               | -           | low       |
| tetraethyl silicate     | 3.18               | -           | low       |
| xylene                  | 3.12               | 8.1 to 25.9 | low       |
| 1-methoxy-2-propanol    | <1                 | -           | low       |
| ethylbenzene            | 3.6                | -           | low       |
| zinc chloride           | -                  | 60960       | high      |

**12.4 Mobility in soil****Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.**Mobility** : Not available.**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

#### Waste catalogue

| Waste code | Waste designation   |
|------------|---|
| 08 01 11*  | Waste paint and varnish containing organic solvents or other dangerous substances |





#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

| Type of packaging | Waste catalogue  |
|-------------------|--|
| CEPE Guidelines   | 15 01 10* packaging containing residues of or contaminated by hazardous substances |

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

|  | ADR/RID  | ADN  | IMDG  | IATA   |
|--|--|--|---|--|
| <b>14.1 UN number</b>                  | UN1263   | UN1263   | UN1263  | UN1263   |
| <b>14.2 UN proper shipping name</b>    | Paint  | Paint  | Paint   | Paint  |
| <b>14.3 Transport hazard class(es)</b> | 3<br> | 3<br> | 3<br> | 3<br> |
| <b>14.4 Packing group</b>              | II   | II   | II  | II   |
| <b>14.5 Environmental hazards</b>      | No.  | Yes.   | No.   | No.  |

#### Additional information

**ADR/RID** : **Hazard identification number** 33  
**Special provisions** 640D  
**Tunnel code** (D/E)

**ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.  
**Special provisions** 640 (C)



Resist 65 Comp A

## SECTION 14: Transport information

**IMDG** : **Emergency schedules** F-E, S-E

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not available.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**UK (GB)/REACH**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Ozone depleting substances**

Not listed.

**Prior Informed Consent (PIC)**

Not listed.

**Persistent Organic Pollutants**

Not listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Seveso Directive**

This product is controlled under the Seveso Directive.

**Danger criteria**

**Category**

P5c

**EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**International regulations**

**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol**

Not listed.

Resist 65 Comp A

## SECTION 15: Regulatory information

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### 15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
 GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = GB CLP-specific Hazard statement  
 N/A = Not available  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 SGG = Segregation Group  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification

| Classification   | Justification   |
|--|---|
| Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>Aquatic Chronic 3, H412 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method |

### Full text of abbreviated H statements

|       |  |
|-------|--|
| ✔H225 | Highly flammable liquid and vapour.                                |
| H226  | Flammable liquid and vapour.                                       |
| H302  | Harmful if swallowed.  |
| H304  | May be fatal if swallowed and enters airways.                      |
| H312  | Harmful in contact with skin.                                      |
| H314  | Causes severe skin burns and eye damage.                           |
| H315  | Causes skin irritation.  |
| H318  | Causes serious eye damage.   |
| H319  | Causes serious eye irritation.                                     |
| H331  | Toxic if inhaled.  |
| H332  | Harmful if inhaled.  |
| H335  | May cause respiratory irritation.                                  |
| H336  | May cause drowsiness or dizziness.                                 |
| H373  | May cause damage to organs through prolonged or repeated exposure. |
| H400  | Very toxic to aquatic life.  |
| H410  | Very toxic to aquatic life with long lasting effects.              |
| H412  | Harmful to aquatic life with long lasting effects.                 |

### Full text of classifications

Resist 65 Comp A

## SECTION 16: Other information

|                   |   |
|-------------------|---|
| Acute Tox. 3      | ACUTE TOXICITY - Category 3                                     |
| Acute Tox. 4      | ACUTE TOXICITY - Category 4                                     |
| Aquatic Acute 1   | SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1                  |
| Aquatic Chronic 1 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1                 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3                 |
| Asp. Tox. 1       | ASPIRATION HAZARD - Category 1                                  |
| Eye Dam. 1        | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1                  |
| Eye Irrit. 2      | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2                  |
| Flam. Liq. 2      | FLAMMABLE LIQUIDS - Category 2                                  |
| Flam. Liq. 3      | FLAMMABLE LIQUIDS - Category 3                                  |
| Skin Corr. 1B     | SKIN CORROSION/IRRITATION - Category 1B                         |
| Skin Irrit. 2     | SKIN CORROSION/IRRITATION - Category 2                          |
| STOT RE 2         | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 3         | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3   |

**Date of printing** : 21.04.2023

**Date of issue/ Date of revision** : 21.04.2023

**Date of previous issue** : 30.03.2023

**Version** : 1.02

### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.