

SAFETY DATA SHEET



Tankguard 412 Comp A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Tankguard 412 Comp A
Product code : 2063
Product description : Paint.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use
Use in coatings - Professional use

1.3 Details of the supplier of the safety data sheet

Jotun A/S
P.O. Box 2021
3202 Sandefjord Norway

Tel: + 47 33 45 70 00
Fax: +47 33 45 72 42
sdsjotun@jotun.no

National contact

Jotun Italia S.r.l.
Via Oliviero Petronio, 8
34015 Muggia (TS)
Italy

Tel: +39 040 23 98 111/23 98 203
Fax: +39 040 4606968
SDSJotun@jotun.com
info@jotun.it

1.4 Emergency telephone number

CAV "Ospedale Pediatrico Bambino Gesù" – Roma - Tel. (+39) 06.6859.3726
CAV "Azienda Ospedaliera Università di Foggia" – Foggia - Tel. 800.183.459
CAV "Azienda Ospedaliera A. Cardarelli" – Napoli - Tel. (+39) 081.545.3333
CAV Policlinico "Umberto I" – Roma - Tel. (+39) 06.4997.8000
CAV Policlinico "A. Gemelli" – Roma - Tel. (+39) 06.305.4343
CAV Azienda Ospedaliera "Careggi" U.O. Tossicologia Medica – Firenze - Tel. (+39) 055.794.7819
CAV Centro Nazionale di Informazione Tossicologica – Pavia - Tel. (+39) 0382.24.444
CAV Ospedale Niguarda – Milano - Tel. (+39) 02.66.1010.29
CAV Azienda Ospedaliera Papa Giovanni XXIII – Bergamo - Tel. 800.88.33.00
CAV Centro Antiveneni Veneto – Verona - Tel. 800.011.858

Tankguard 412 Comp A

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315

Eye Irrit. 2, H319

Skin Sens. 1, H317

Muta. 2, H341

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Warning.

Hazard statements :

- H315 - Causes skin irritation.
- H317 - May cause an allergic skin reaction.
- H319 - Causes serious eye irritation.
- H341 - Suspected of causing genetic defects.
- H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention :

- P201 - Obtain special instructions before use.
- P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.
- P273 - Avoid release to the environment.
- P261 - Avoid breathing vapour.

Response :

- P391 - Collect spillage.
- P308 + P313 - IF exposed or concerned: Get medical advice or attention.
- P362 + P364 - Take off contaminated clothing and wash it before reuse.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients :

- epoxy resin (MW ≤ 700)
- 2,3-epoxypropyl neodecanoate

Supplemental label elements :

- EUH205 - Contains epoxy constituents. May produce an allergic reaction.
- EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Tankguard 412 Comp A

SECTION 2: Hazards identification

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.


The mixture may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
epoxy resin (MW ≤ 700)	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
2,3-epoxypropyl neodecanoate	REACH #: 01-2119431597-33 EC: 247-979-2 CAS: 26761-45-5	≤10	Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411	-	[1]
complex mixture of diamid waxes	REACH #: 01-0000017860-69 EC: 432-430-3	≤3	Aquatic Chronic 4, H413 See Section 16 for the full text of the H statements declared above.	-	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

 Substance classified with a health or environmental hazard

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Tankguard 412 Comp A

SECTION 4: First aid measures

- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

Tankguard 412 Comp A

SECTION 7: Handling and storage

See Technical Data Sheet / packaging for further information.

7.3 Specific end use(s)**Recommendations** : Not available.**Industrial sector specific solutions** : Not available.**SECTION 8: Exposure controls/personal protection**

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

No exposure limit value known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
 European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
epoxy resin (MW ≤ 700) 2,3-epoxypropyl neodecanoate	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	2.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	4 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	4.2 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	5.88 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	2.5 mg/kg bw/day	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
epoxy resin (MW ≤ 700) 2,3-epoxypropyl neodecanoate	Fresh water	0.006 mg/l	-
	Marine	0.0006 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	0.996 mg/l	-
	Marine water sediment	0.0996 mg/l	-
	Soil	0.196 mg/l	-
	Fresh water	0.0012 mg/l	-
	Marine	0.00012 mg/l	-

Tankguard 412 Comp A

SECTION 8: Exposure controls/personal protectionSewage Treatment
Plant

50 mg/l

-

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection**Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm), nitrile rubber (> 0.75 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm), butyl rubber (> 0.4 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use a respirator according to EN 140. Use respiratory mask with charcoal and dust filter when spraying this product, according to EN 14387 (as filter combination A2-P2). In confined spaces, use compressed-air or fresh-air respiratory equipment. When use of roller or brush, consider use of charcoalfilter.

Environmental exposure controls : Do not allow to enter drains or watercourses.

Tankguard 412 Comp A

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties**Appearance**

Physical state	: Liquid.
Colour	: Black, Green., Red, White.
Odour	: Characteristic.
Odour threshold	: Not applicable.
Melting point/freezing point	: <input checked="" type="checkbox"/> Not available.
Initial boiling point and boiling range	: Lowest known value: >260°C (>500°F)(epoxy resin (MW ≤ 700)).
Flammability	: Not applicable.
Lower and upper explosion limit	: <input checked="" type="checkbox"/> Not available.
Flash point	: Closed cup: 100°C
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
pH	: Not applicable.
Viscosity	: Kinematic (40°C): >20.5 mm ² /s
Solubility in water	: cold water Not soluble hot water Not soluble
Partition coefficient: n-octanol/ water	: Not available.
Vapour pressure	: Highest known value: 0.01 kPa (0.1 mm Hg) (at 20°C) (2,3-epoxypropyl neodecanoate). Weighted average: 0.002 kPa (0.02 mm Hg) (at 20°C)
Evaporation rate	: Not available.
Density	: 1.72 to 1.77 g/cm ³
Vapour density	: Highest known value: 11.7 (Air = 1) (epoxy resin (MW ≤ 700)).
Explosive properties	: Not available.
Oxidising properties	: Not available.
<u>Particle characteristics</u>	
Median particle size	: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Tankguard 412 Comp A

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
epoxy resin (MW ≤ 700)	LD50 Dermal	Rabbit	20 g/kg	-
	LD50 Oral	Mouse	15600 mg/kg	-
2,3-epoxypropyl neodecanoate	LD50 Oral	Rat	>10 g/kg	-

Acute toxicity estimates

N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
epoxy resin (MW ≤ 700)	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
2,3-epoxypropyl neodecanoate	Skin - Moderate irritant	Rabbit	-	0.5 Milliliters	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
epoxy resin (MW ≤ 700)	skin	Mammal - species unspecified	Sensitising
2,3-epoxypropyl neodecanoate	skin	Mammal - species unspecified	Sensitising

Skin : May cause an allergic skin reaction.

Mutagenicity

Conclusion/Summary : Suspected of causing genetic defects.

Suspected of causing genetic defects.

Carcinogenicity

No known significant effects or critical hazards.

Reproductive toxicity

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

Tankguard 412 Comp A

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
epoxy resin (MW ≤ 700)	Acute EC50 1.4 mg/l Acute LC50 3.1 mg/l Chronic NOEC 0.3 mg/l	Daphnia Fish - pimephales promelas Fish	48 hours 96 hours 21 days

Conclusion/Summary : This material is toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
epoxy resin (MW ≤ 700)	-	-	Not readily
2,3-epoxypropyl neodecanoate	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
epoxy resin (MW ≤ 700)	2.64 to 3.78	31	low
2,3-epoxypropyl neodecanoate	4.4	-	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

Tankguard 412 Comp A

SECTION 13: Disposal considerations

Disposal considerations : Do not allow to enter drains or watercourses.
 Dispose of according to all federal, state and local applicable regulations.
 If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.
 For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

Packaging









Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.
 Empty containers must be scrapped or reconditioned.
 Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Type of packaging	European waste catalogue (EWC)
CEPE Guidelines	15 01 10* packaging containing residues of or contaminated by hazardous substances

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), 2,3-epoxypropyl neodecanoate)	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), 2,3-epoxypropyl neodecanoate)	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), 2,3-epoxypropyl neodecanoate). Marine pollutant (epoxy resin (MW ≤ 700), 2,3-epoxypropyl neodecanoate)	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin (MW ≤ 700), 2,3-epoxypropyl neodecanoate)
14.3 Transport hazard class(es)	9  	9  	9  	9  
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

Tankguard 412 Comp A

SECTION 14: Transport information

ADR/RID	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Hazard identification number 90 Tunnel code (-)
ADN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
IMDG	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F
IATA	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
UN	: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
14.6 Special precautions for user	: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Maritime transport in bulk according to IMO instruments	: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC	: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
VOC for Ready-for-Use Mixture	: Not available.
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed

Tankguard 412 Comp A

SECTION 15: Regulatory information

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

National regulations

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

D.Lgs. 152/06 : Not determined.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment : Not applicable.

SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number
 SGG = Segregation Group
 vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Tankguard 412 Comp A**SECTION 16: Other information**

Classification	Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411	Calculation method Calculation method Calculation method Calculation method Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS]

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

Date of printing : 22.07.2025**Date of issue/ Date of revision** : 22.07.2025**Date of previous issue** : 22.03.2023**Version** : 1.02**Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.