SAFETY DATA SHEET



SteelMaster 1200WF

Section 1. Identification

GHS product identifier : SteelMaster 1200WF

Product code : 25780

Other means of identification

: Not available.

Product type : Liquid.

Product description : Waterborne paint.

Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use
Use in coatings - Professional use

Supplier's details : 佐敦涂料(张家港)有限公司

江苏省张家港保税区扬子江化学工业园长江路15号 215634

电话: +86 512 58937988 传真: +86 512 58937986

Jotun Coatings (Zhangjiagang) Co. Ltd

No.15 Changjiang Road Jiangsu Yangtze River International Chemical Industry Park,

Zhangjiagang Free Trade Zone, Jiangsu Province 215634

Tel: +86 512 58937988 Fax: +86 512 58937986

Jotun Paints (Malaysia) Sdn Bhd, Lot 7 Persiaran Perusahaan, Section 23

40300 SHAH ALAM, Selangor Darul Ehsan

Malaysia

Tel: +603 51235500 Fax: +603 51235599

SDSJotun@jotun.com

Emergency telephone number (with hours of

operation)

: Jotun Coatings (Taiwan) Ltd. Co. Tel: +886 2 87705061

Section 2. Hazards identification

Classification of the substance or mixture

: CARCINOGENICITY - Category 2 REPRODUCTIVE TOXICITY - Category 2

GHS label elements

Hazard pictograms



Signal word : Warning.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 1/12

Section 2. Hazards identification

Hazard statements : H351 - Suspected of causing cancer.

H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing and eye or face protection.

Response : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture Other means of

identification

: Not available.

| Product name | % (w/w) | CAS number | Type |
|--|---------|--------------------|------|
| melamine | <10 | 108-78-1 | [1] |
| C(M)IT/MIT (3:1) | <0.0025 | 55965-84-9 | [1] |
| 物品名稱 | % (w/w) | 化學文摘社登記號碼(CAS No.) | 類型 |
| melamine | <10 | 108-78-1 | [1] |
| 5-氯-2-甲基-1-异噻唑啉-3-酮和 2-甲基-1-异噻唑啉 -3-酮的混合物 | <0.0025 | 55965-84-9 | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide

artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance

for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 25.11.2024 : 26.06.2024 Version: 1.08 2/12 Date of previous issue

Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides metal oxide/oxides

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 3/12

Section 5. Firefighting measures

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 4/12

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Hand protection

: There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: nitrile rubber (> 0.75 mm), neoprene (> 0.35 mm), PVC (> 0.5 mm)

May be used, gloves(breakthrough time) 4 - 8 hours: 4H/Silver Shield® (> 0.07 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Eye protection

: Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 5/12

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. Colour : White.

: Characteristic. **Odour Odour threshold** : Not available.

: 8 to 9 pН **Melting point/freezing point**

Boiling point, initial boiling

: Not available.

point, and boiling range

Flash point

| | | Closed cup | | | Open cup | | |
|--|------|------------|------------------|-------|----------|--------|--|
| Ingredient name | °C | °F | Method | °C | °F | Method | |
| propan-2-ol | 11.7 | 53.1 | | 11.85 | 53.3 | | |
| formic acid | 49.5 | 121.1 | DIN EN ISO 13736 | | | | |
| 2-amino-2-methylpropanol | 82.1 | 179.8 | EU A.9 | | | | |
| propylene glycol | 99 | 210.2 | | | | | |
| glyoxal | >100 | >212 | | | | | |
| propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl- 1,3-pentanediol | 122 | 251.6 | ASTM 3278 | 120 | 248 | | |
| propylidynetrimethanol | 172 | 341.6 | | | | | |

Flammability

: Not available.

Lower and upper explosion

: Not applicable.

limit/flammability limit

Vapour pressure

| | Var | Vapour Pressure at 20°C | | Va | oour pressu | re at 50°C |
|--|-------------|-------------------------|-------------|----------|-------------|------------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| propan-2-ol | 33.00268 | 4.4 | | | | |
| formic acid | 32.03522 | 4.3 | EU A.4 | | | |
| water | 17.5 | 2.3 | | | | |
| glyoxal | 15.15129 | 2 | EU A.4 | | | |
| 2-amino-2-methylpropanol | 0.33753 | 0.045 | ASTM E 1194 | | | |
| propylene glycol | 0.15 | 0.02 | EU A.4 | | | |
| propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl- 1,3-pentanediol | 0.0098 | 0.0013 | EU A.4 | | | |
| propanol, oxybis-, dibenzoate | 0.0000012 | 0.00000016 | EU A.4 | 0.000011 | 0.0000015 | EU A.4 |
| pentaerythritol | 0.000000026 | 0.000000035 | | | | |
| polyphosphoric acids, ammonium salts | 0 | 0 | | | | |
| 1,3-propanediol, 2,2'-[oxybis (methylene)]bis[2-(hydroxymethyl)- | 0 | 0 | | | | |
| propylidynetrimethanol | 0 | 0 | | | | |

Relative vapour density : Not available. **Density** : 1.409 g/cm³

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 6/12

Section 9. Physical and chemical properties and safety characteristics

Solubility(ies)

| Media | Result |
|-------------------------|-------------------------------|
| cold water hot water | Easily soluble Easily soluble |

Partition coefficient: n-

: Not applicable.

octanol/water

Auto-ignition temperature

| Ingredient name | °C | °F | Method |
|---|------|-------|-------------|
| glyoxal | 285 | 545 | DIN 51794 |
| propylene glycol | 371 | 699.8 | |
| propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol | 393 | 739.4 | |
| formic acid | 434 | 813.2 | |
| 2-amino-2-methylpropanol | 438 | 820.4 | ASTM D 2161 |
| melamine | >400 | >752 | EU A.16 |
| pentaerythritol | >400 | >752 | EU A.16 |
| propanol, oxybis-, dibenzoate | >400 | >752 | EU A.15 |
| 1,3-propanediol, 2,2'-[oxybis(methylene)]bis[2-(hydroxymethyl)- | >400 | >752 | EU A.16 |
| propan-2-ol | 456 | 852.8 | |

Decomposition temperature: Not available.

Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

: Under normal conditions of storage and use, hazardous decomposition products

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|------------------------------|------------------------|---------|------------------------|----------|
| melamine C(M)IT/MIT (3:1) | LD50 Oral LD50 Oral | | 3161 mg/kg 53 mg/kg | - |

Irritation/Corrosion

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 7/12

Section 11. Toxicological information

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|----------------------|---------|-------|--------------|-------------|
| melamine | Eyes - Mild irritant | Rabbit | | 24 hours 500 | - |
| | | | | milligrams | |

Sensitisation

| 3 | Route of exposure | Species | Result |
|------------------|-------------------|------------------------------|-------------|
| C(M)IT/MIT (3:1) | skin | Mammal - species unspecified | Sensitising |

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Developmental toxin | Species | Dose | Exposure |
|-------------------------|-------------------|-----------|---------------------|---------|-------------------|----------|
| melamine | - | Positive | - | | Oral: 89 mg/kg | days |

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | | Route of exposure | Target organs |
|-------------------------|------------|-------------------|---------------|
| melamine | Category 2 | - | urinary tract |

Aspiration hazard

Not available.

Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Skin contact** Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

> reduced foetal weight increase in foetal deaths skeletal malformations

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 8/12 Version : 1.08

Section 11. Toxicological information

Ingestion : Adverse symptoms may include the following:

reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

| | (3 | (mg/kg) | (0) | (vapours) | Inhalation (dusts and mists) (mg/l) |
|------------------|-----|---------|-----|-----------|--|
| C(M)IT/MIT (3:1) | 53 | 50 | N/A | 0.5 | N/A |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------|---|----------|
| C(M)IT/MIT (3:1) | Acute EC50 0.048 mg/l | Algae - Pseudokirchneriella subcapitata | 72 hours |
| | Acute EC50 0.0052 mg/l | Algae - Skeletonema costatum | 48 hours |
| | Acute EC50 0.1 mg/l | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 0.22 mg/l | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute NOEC 0.00064 mg/l | Algae - Skeletonema costatum | 48 hours |
| | Chronic NOEC 0.0012 mg/l | Algae - Pseudokirchneriella subcapitata | 72 hours |
| | Chronic NOEC 0.004 mg/l | Daphnia - Daphnia magna | 21 days |
| | Chronic NOEC 0.098 mg/l | Fish - Oncorhynchus mykiss | 28 days |

Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| C(M)IT/MIT (3:1) | - | - | Not readily |

Bioaccumulative potential

Section 12. Ecological information

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| melamine | -1.22 | | low |
| C(M)IT/MIT (3:1) | - | | low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | UN | IMDG | IATA |
|----------------------------|----------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - |
| Transport hazard class(es) | - | - | - |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available. to IMO instruments

Date of issue/Date of revision : 25.11.2024 : 26.06.2024 Version : 1.08 10/12 Date of previous issue

Section 15. Regulatory information

TCCSCA List of toxic chemicals

| Listed no. | Series no. | Ingredient name | RQ | Class 1 | Class 2 | Class 3 | Class 4 |
|------------|------------|-----------------|----|---------|---------|---------|---------|
| 185 | 1 | melamine | - | - | - | - | Listed |

TCCSCA List of concerned chemicals

Not applicable.

OSHA Enforcement Rules

Article 28

: This product contains substances "Specially hazardous to health": propan-2-ol.

Priority management chemicals, Article 2

Chemical substances possessing physical hazards or health hazards (Article 2.2 (II))

| Ingredient name | Name on list | Concentration |
|-----------------|-------------------|---------------|
| propan-2-ol | isopropyl alcohol | ≤1 |

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

Procedure used to derive the classification

| Classification | Justification | |
|---|---------------------------------------|--|
| CARCINOGENICITY - Category 2 REPRODUCTIVE TOXICITY - Category 2 | Calculation method Calculation method | |

References : Not available.

Organisation that prepared : Jotun AS, Norway +47 33 45 70 00

History

Date of printing : 25.11.2024

Date of previous issue : 26.06.2024

Version : 1.08

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 11/12

Section 16. Other information

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 12/12