

SAFETY DATA SHEET



Hardtop Pro Comp A

Section 1. Identification

Product identifier	: Hardtop Pro Comp A
Product code	: 27220
Other means of identification	: Not available.
Product type	: Liquid.
Product description	: Paint.

Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Professional use

Supplier's details	: Jotun (Singapore) Pte Ltd 37 Tuas View Crescent Singapore 637236 Phone: 6508 8288 Fax: 6265 7484 SDSJotun@jotun.com
Emergency telephone number (with hours of operation)	: Jotun (Singapore) Pte Ltd, Tel: 6508 8288

Section 2. Hazards identification

Classification of the substance or mixture	: FLAMMABLE LIQUIDS - Category 3 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
---	---

GHS label elements, including precautionary statements

Hazard pictograms :



Signal word : Warning.

Hazard statements : H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS))
H412 - Harmful to aquatic life with long lasting effects.

Section 2. Hazards identification

Precautionary statements

- General** : Not applicable.
- Prevention** : P280 - Wear protective gloves.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P260 - Do not breathe vapour.
- Response** : P314 - Get medical advice/attention if you feel unwell.
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
- Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

Ingredient name	%	CAS number
n-butyl acetate	≥10 - ≤25	123-86-4
hydrocarbons, C9, aromatics	≤9.6	64742-95-6
xylene	≤5	1330-20-7
ethylbenzene	≤3	100-41-4
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	≤1.7	64742-82-1
decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester, mixt. with 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidiny) decanedioate	≤1	1065336-91-5
fatty acids, C14-18 and C16-18-unsatd., maleated	<1	85711-46-2
n-butyl acrylate	≤0.3	141-32-2
Oleic acid, compound	≤0.1	34140-91-5
maleic anhydride	≤0.1	108-31-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Chemical formula : Not applicable.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : May cause drowsiness or dizziness.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.

- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
n-butyl acetate	Workplace Safety and Health Act (Singapore, 2/2006). PEL (short term): 950 mg/m ³ 15 minutes. PEL (short term): 200 ppm 15 minutes. PEL (long term): 713 mg/m ³ 8 hours. PEL (long term): 150 ppm 8 hours.
xylene	Workplace Safety and Health Act (Singapore, 2/2006). [Xylene] PEL (short term): 651 mg/m ³ 15 minutes. PEL (short term): 150 ppm 15 minutes.

Section 8. Exposure controls/personal protection

ethylbenzene	<p>PEL (long term): 434 mg/m³ 8 hours. PEL (long term): 100 ppm 8 hours. Workplace Safety and Health Act (Singapore, 2/2006). Notes: PEL (long term): 100 ppm 8 hours. PEL (long term): 434 mg/m³ 8 hours. Workplace Safety and Health Act (Singapore, 2/2006). PEL (short term): 543 mg/m³ 15 minutes. PEL (short term): 125 ppm 15 minutes.</p>
n-butyl acrylate	<p>Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 10 ppm 8 hours. PEL (long term): 52 mg/m³ 8 hours.</p>
maleic anhydride	<p>Workplace Safety and Health Act (Singapore, 2/2006). PEL (long term): 0.25 ppm 8 hours. PEL (long term): 1 mg/m³ 8 hours.</p>

Biological exposure indices

No exposure indices known.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Section 8. Exposure controls/personal protection

Wear suitable gloves tested to ISO 374-1:2016.

Not recommended, gloves(breakthrough time) < 1 hour: Viton® (> 0.7 mm)

May be used, gloves(breakthrough time) 4 - 8 hours: neoprene (> 0.35 mm), butyl rubber (> 0.4 mm), PVC (> 0.5 mm)

Recommended, gloves(breakthrough time) > 8 hours: 4H/Silver Shield® (> 0.07 mm), Teflon (> 0.35 mm), nitrile rubber (> 0.75 mm), polyvinyl alcohol (PVA) (> 0.3 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

- : Use chemical-resistant protective suit / disposable overall.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

- : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

- : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

: Liquid.

Colour

: Blue., Green., Grey, MCI Base 1, MCI Base 2, MCI Base 3, MCI Base 5, MCI Base 6, Off-white., Orange, Red, White., Yellow.

Odour

: Characteristic.

Odour threshold

: Not available.

pH

: Not applicable.

Melting point/freezing point

: Not applicable.

Boiling point, initial boiling point, and boiling range

: Lowest known value: 126°C (258.8°F) (n-butyl acetate). Weighted average: 138.62°C (281.5°F)

Flash point

: Closed cup: 28°C (82.4°F)

Evaporation rate

: Highest known value: 1 (n-butyl acetate) Weighted average: 0.91 compared with butyl acetate

Flammability

: Not applicable.

Lower and upper explosion limit/flammability limit

: Greatest known range: Lower: 1.4% Upper: 7.6% (n-butyl acetate)

Vapour pressure

: Highest known value: 2.7 kPa (20.3 mm Hg) (at 20°C) (hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)). Weighted average: 1.21 kPa (9.08 mm Hg) (at 20°C)

Relative vapour density

: Highest known value: 4 (Air = 1) (n-butyl acetate). Weighted average: 3.93 (Air = 1)

Density

: 1.307 to 1.496 g/cm³

Solubility(ies)

:

Section 9. Physical and chemical properties and safety characteristics

Media	Result
cold water	Not soluble
hot water	Not soluble

Partition coefficient: n-octanol/water : Not available.

Auto-ignition temperature : Lowest known value: 280 to 470°C (536 to 878°F) (hydrocarbons, C9, aromatics).

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C): >20.5 mm²/s

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SADT : Not available.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	13100 mg/kg	-
xylene	LC50 Inhalation Vapour	Rat	11 mg/l	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
	TDLo Dermal	Rabbit	4300 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat - Male	11 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
maleic anhydride	LD50 Oral	Rat	400 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Eyes - Mild irritant Skin - Mild irritant	Rabbit Rat	- -	87 milligrams 8 hours 60 microliters	- -
fatty acids, C14-18 and C16-18-unsatd., maleated	Skin - Mild irritant	Mammal - species unspecified	-	-	-
n-butyl acrylate	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
maleic anhydride	Eyes - Severe irritant	Rabbit	-	1 Percent	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
fatty acids, C14-18 and C16-18-unsatd., maleated	skin	Mammal - species unspecified	Sensitising
n-butyl acrylate	skin	Mammal - species unspecified	Sensitising
maleic anhydride	skin	Mammal - species unspecified	Sensitising

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-butyl acetate hydrocarbons, C9, aromatics	Category 3 Category 3	- -	Narcotic effects Respiratory tract irritation
xylene	Category 3 Category 3	- -	Narcotic effects Respiratory tract irritation
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 3	-	Narcotic effects
n-butyl acrylate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Category 2 Category 1	- -	hearing organs central nervous system (CNS)
Oleic acid, compound maleic anhydride	Category 2 Category 1 Category 2	- inhalation	- respiratory system

Aspiration hazard

Section 11. Toxicological information

Product/ingredient name	Result
hydrocarbons, C9, aromatics xylene ethylbenzene hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : May cause drowsiness or dizziness.
Skin contact : May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
Inhalation : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
Skin contact : Adverse symptoms may include the following:
irritation
redness
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Hardtop Pro Comp A	N/A	27959.7	N/A	208.4	N/A
n-butyl acetate	13100	N/A	N/A	N/A	N/A
xylene	4300	1100	N/A	11	N/A
ethylbenzene	3500	N/A	N/A	11	N/A
n-butyl acrylate	N/A	N/A	N/A	11	N/A
maleic anhydride	400	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
hydrocarbons, C9, aromatics	Acute EC50 <10 mg/l	Daphnia	48 hours
	Acute IC50 <10 mg/l	Algae	72 hours
	Acute LC50 <10 mg/l	Fish	96 hours
xylene	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
ethylbenzene	Acute EC50 7700 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 2.93 mg/l	Daphnia	48 hours
	Acute LC50 4.2 mg/l	Fish	96 hours
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Acute EC50 <10 mg/l	Daphnia	48 hours
	Acute IC50 <10 mg/l	Algae	72 hours
	Acute LC50 <10 mg/l	Fish	96 hours
decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester, mixt. with 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidiny) decanedioate	Acute EC50 1.68 mg/l	Algae	96 hours
	Acute LC50 0.9 mg/l	Fish	96 hours
	Chronic NOEC 1 mg/l	Daphnia	21 days
maleic anhydride	Acute LC50 230 ppm Fresh water	Fish - Gambusia affinis - Adult	96 hours

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
hydrocarbons, C9, aromatics	-	-	Not readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	-	-	Not readily

Bioaccumulative potential

Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
n-butyl acetate	2.3	-	low
hydrocarbons, C9, aromatics	-	10 to 2500	high
xylene	3.12	8.1 to 25.9	low
ethylbenzene	3.6	-	low
hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	-	10 to 2500	high
n-butyl acrylate	2.38	17.27	low
maleic anhydride	-2.78	-	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA	ADR/RID	ADN
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	Paint	Paint	Paint	Paint	Paint
Transport hazard class (es)	3 	3 	3 	3 	3 
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	Yes.

Additional information

UN: Viscous substance. Not goods of class 3, ref. 2.3.2.5 (only applicable to receptacles < 450 litre capacity).

IMDG : **Emergency schedules** F-E, S-E

IMDG: Viscous substance. Transport in accordance with 2.3.2.5 of the IMDG Code (only applicable to receptacles < 450 litre capacity).

Section 14. Transport information

- ADR/RID** : **Hazard identification number** 30
Tunnel code (D/E)
 ADR/RID: Viscous substance. Not goods of class 3, ref. 2.2.3.1.5 (only applicable to receptacles < 450 litre capacity).
- ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- Transport in bulk according to IMO instruments** : Not available.

Section 15. Regulatory information

Singapore - hazardous chemicals under government control

None.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

History

- Date of printing** : 05.07.2024
- Date of issue/Date of revision** : 05.07.2024
- Date of previous issue** : No previous validation
- Version** : 1
- Key to abbreviations** : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 UN = United Nations

Procedure used to derive the classification

Section 16. Other information

Classification	Justification
FLAMMABLE LIQUIDS - Category 3 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	On basis of test data Calculation method Calculation method Calculation method Calculation method

References : Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.