# **SAFETY DATA SHEET**



### **Megafiller Smooth Comp B**

## Section 1. Chemical product and company identification

**Product name** : Megafiller Smooth Comp B

Product code : 2907
Product type : Solid.

**Product description**: Hardener. Putty.

#### Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use

Supplier's details : 佐敦涂料(张家港)有限公司

中国江苏扬子江国际化学工业园南海路39号 215634

电话: +86 512 58937988 传真: +86 512 58937986

Jotun Coatings (Zhangjiagang) Co. Ltd

NO.39 Nanhai Road Jiangsu Yangtze River International Chemical Industry Park,

Jiangsu Province 215634 China

Tel: +86 512 58937988 Fax: +86 512 58937986

中远佐敦船舶涂料(青岛)有限公司中国山东省青岛市高新区春阳路800号

总机电话: +86-532-68689888 总机传真: +86-532-66726750

Jotun COSCO Marine Coatings (Qingdao) Co. Ltd.

No. 800, Chunyang Road, High-tech Zone, Qingdao, P. R. China

Tel: +86-532-68689888 Fax: +86-532-66726750

SDSJotun@jotun.com

Emergency telephone number (with hours of operation)

: Emergency Services for Chemical Incident of China. Tel: +86 532 83889090

## Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SKIN SENSITISATION - Category 1

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 1/12

# Section 2. Hazards identification

#### **GHS label elements**

Hazard pictograms





Signal word : Danger.

**Hazard statements**: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

General : Not applicable.

**Prevention**: P280 - Wear protective gloves. Wear eye or face protection.

P273 - Avoid release to the environment.

P261 - Avoid breathing dust.

**Response** : P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Physical and chemical

hazards

: No known significant effects or critical hazards.

Health hazards : Causes skin irritation. May cause an allergic skin reaction. Causes serious eye

damage.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of : Not availa

identification

: Not available.

Ingredient name	%	CAS number
triethylenetetramine	<25	68082-29-1
benzyl alcohol	≤14	100-51-6
formaldehyde, polymer with benzenamine, hydrogenated	≤1.7	135108-88-2
Amines, polyethylenepoly-, triethylenetetramine fraction	≤1.7	90640-67-8
2,4,6-tris(dimethylaminomethyl)phenol	≤1.4	90-72-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 2/12

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 3/12

## Section 4. First aid measures

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing media

Unsuitable extinguishing media

: None known.

metal oxide/oxides

Specific hazards arising from the chemical

: This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

: Use an extinguishing agent suitable for the surrounding fire.

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and material for containment and cleaning up

**Small spill** 

: Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 4/12

## Section 7. Handling and storage

#### **Precautions for safe handling**

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

None.

#### **Biological exposure indices**

No exposure indices known.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

#### **Skin protection**

Hand protection

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 5/12

# Section 8. Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove

material.

Always ensure that gloves are free from defects and that they are stored and used

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to ISO 374-1:2016.

Not recommended, gloves(breakthrough time) < 1 hour: PVC (> 0.5 mm)

May be used, gloves(breakthrough time) 4 - 8 hours: polyvinyl alcohol (PVA) (> 0.3 mm), nitrile rubber (> 0.75 mm)

Recommended, gloves(breakthrough time) > 8 hours: Viton® (> 0.7 mm), 4H/Silver Shield® (> 0.07 mm), neoprene (> 0.35 mm), butyl rubber (> 0.4 mm)

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Use chemical-resistant protective suit / disposable overall.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a

respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state
Colour
Colour
Colour
Codour
Codour
Codour
Codour threshold

point, and boiling range

Flash point : Closed cup: 105°C (221°F) [Setaflash]

Evaporation rate : Not available.

Flammability : Not applicable.

Lower and upper explosion : Not available.

limit/flammability limit

Vapour pressure : Highest known value: 0 kPa (0 mm Hg) (at 20°C) (talc (non-asbestos form)).

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 6/12

# Section 9. Physical and chemical properties and safety characteristics

**Relative vapour density** : Not available. **Density** : 1.688 g/cm³

Solubility(ies) :

Media	Result
cold water hot water	Not soluble Not soluble

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

**Particle characteristics** 

Median particle size : Not available.

No additional information.

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	LD50 Oral	Rat	1230 mg/kg	-
formaldehyde, polymer with benzenamine, hydrogenated	LD50 Oral	Rat	300 mg/kg	-
Amines, polyethylenepoly-, triethylenetetramine fraction	LD50 Dermal	Rabbit - Male, Female	1465.4 mg/kg	-
	LD50 Oral	Rat - Male, Female	1716.2 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Oral	Rat	1673 mg/kg	-

**Irritation/Corrosion** 

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 7/12

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	Eyes - Irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-
benzyl alcohol	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
2,4,6-tris (dimethylaminomethyl) phenol	Eyes - Severe irritant	Rabbit	-	24 hours 50 μg	-
	Skin - Severe irritant	Rat	-	0.25 ml	-

#### **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	skin	Mammal - species unspecified	Sensitising
Amines, polyethylenepoly-, triethylenetetramine fraction	skin	Mammal - species unspecified	Sensitising

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name		Route of exposure	Target organs
formaldehyde, polymer with benzenamine, hydrogenated	Category 2	oral	kidneys

#### **Aspiration hazard**

Not available.

Information on likely routes : Not available.

of exposure

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

**Skin contact** : Causes skin irritation. May cause an allergic skin reaction.

: No known significant effects or critical hazards. Ingestion

#### Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 8/12

# Section 11. Toxicological information

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion**: Adverse symptoms may include the following:

stomach pains

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

Potential immediate : Not

effects

: Not available.

Potential delayed effects

: Not available.

**Long term exposure** 

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Megafiller Smooth Comp B benzyl alcohol formaldehyde, polymer with benzenamine, hydrogenated	5970.2 1230 300	86940.0 N/A N/A	N/A N/A N/A	11	N/A N/A N/A
Amines, polyethylenepoly-, triethylenetetramine fraction 2,4,6-tris(dimethylaminomethyl)phenol	1716.2 2500	1465.4 N/A	N/A N/A		N/A N/A

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Amines, polyethylenepoly-, triethylenetetramine fraction	Acute EC50 20 mg/l	Algae	72 hours
·	Acute EC50 31.1 mg/l Acute LC50 330 mg/l	Daphnia Fish	48 hours 96 hours

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 9/12

# Section 12. Ecological information

#### Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol Amines, polyethylenepoly-, triethylenetetramine fraction	-		Readily Not readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	<100	low
formaldehyde, polymer with	-	209 to 219	low
benzenamine, hydrogenated			
Amines, polyethylenepoly-,	-2.65	-	low
triethylenetetramine fraction			
2,4,6-tris	0.219	-	low
(dimethylaminomethyl)phenol			

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	China	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 10/12

# Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

**Incompatible materials** : No specific data.

Transport in bulk according: Not available.

to IMO instruments

: None known.

## Section 15. Regulatory information

Safety, health and environmental regulations specific for the product:

### Law of the People's Republic of China on the Prevention and Control of Occupational Diseases

Regulations on the Control over Safety of Dangerous Chemicals

Measures for Environmental Management of New Chemical Substances

Law of the People's Republic of China on the Prevention and Control of Environment Pollution Caused by Solid Wastes Safety regulations for the use of chemicals in the workplace

General Rule for Classification and Hazard Communication of Chemicals

Classification and code of dangerous goods

#### List of Goods banned for Importing

None of the components are listed.

#### **Drug Precursors Requiring an Import/Export License**

None of the components are listed.

#### **Inventory of Hazardous Chemicals**

None of the components are listed.

#### **List of Explosive Precursors**

None of the components are listed.

#### List of Goods banned for Exporting

None of the components are listed.

#### List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

None of the components are listed.

#### Catalogue and classification of drug precursor chemicals

None of the components are listed.

#### **Inventory of highly toxic articles**

None of the components are listed.

#### Catalogue of Hazardous Chemicals of Priority Management

None of the components are listed.

#### Catalogue of Occupational Disease Hazard Factors - Dust

None of the components are listed.

#### Catalogue of Occupational Disease Hazard Factors - Chemical Factors

None of the components are listed.

#### International regulations

**Chemical Weapon Convention List Schedules I, II & III Chemicals** 

Date of issue/Date of revision : 25.11.2024 : 05.07.2024 Version: 1.06 11/12 Date of previous issue

# Section 15. Regulatory information

Not listed

#### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

### Section 16. Other information

#### **History**

Date of printing : 25.11.2024

Date of issue/Date of : 25.11.2024

revision

Date of previous issue : 05.07.2024

Version : 1.06

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

#### Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3	Calculation method
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3	Calculation method

References : Not available.

▼ Indicates information that has changed from previously issued version.

#### Notice to reader

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 05.07.2024 Version : 1.06 12/12