

SAFETY DATA SHEET



Jotun Protects Property

Jotamastic 70 Comp A

Section 1. Identification

GHS product identifier : Jotamastic 70 Comp A

Product code : 35682

Product description : Paint.

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Professional use

Supplier's details : Jotun Paints Inc.
16223 Park Row Drive, Suite 120
Houston, TX
77084

Phone number: +1 832 615 5646
SDSJotun@jotun.com

Emergency telephone number (with hours of operation) : 1-800-424-9300
(Staffed 24/7)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
AQUATIC HAZARD (LONG-TERM) - Category 3

GHS label elements

Hazard pictograms :



Signal word : Warning.

Hazard statements : H226 - Flammable liquid and vapor.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H373 - May cause damage to organs through prolonged or repeated exposure. (hearing organs)
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Date of issue : 18.07.2024

1/16

Section 2. Hazards identification

- Prevention** : P280 - Wear protective gloves. Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P260 - Do not breathe vapor or spray.
- Response** : P314 - Get medical advice or attention if you feel unwell.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice or attention.
- Storage** : P403 + P235 - Store in a well-ventilated place. Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

- CAS number** : Not applicable.
- Product code** : 35682

Ingredient name	%	CAS number
epoxy resin (MW ≤ 700)	≥10 - <25	1675-54-3
xylene	≤10	1330-20-7
Phenol, methylstyrenated	≤10	68512-30-1
epoxy resin (MW 700-1200)	≤5	25036-25-3
benzyl alcohol	≤5	100-51-6
2-methylpropan-1-ol	<3	78-83-1
ethylbenzene	≤3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Section 4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly

Section 7. Handling and storage

closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
epoxy resin (MW ≤ 700) xylene	None OSHA PEL (United States, 5/2018). [Xylenes] TWA: 435 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). [Xylenes (o-, m-, p-isomers)] STEL: 655 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 435 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. CAL OSHA PEL (United States, 5/2018). [xylene] STEL: 655 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. C: 300 ppm TWA: 435 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. ACGIH TLV (United States, 7/2023). [p-xylene and mixtures containing p-xylene] Ototoxicant. TWA: 20 ppm 8 hours.
Phenol, methylstyrenated epoxy resin (MW 700-1200) benzyl alcohol	None None OARS WEEL (United States, 4/2022). TWA: 10 ppm 8 hours. ACGIH TLV (United States, 7/2023). TWA: 152 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2020). TWA: 150 mg/m ³ 10 hours. TWA: 50 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 300 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.
2-methylpropan-1-ol	

Section 8. Exposure controls/personal protection

ethylbenzene

OSHA PEL 1989 (United States, 3/1989).
 TWA: 150 mg/m³ 8 hours.
 TWA: 50 ppm 8 hours.
CAL OSHA PEL (United States, 5/2018).
 TWA: 150 mg/m³ 8 hours.
 TWA: 50 ppm 8 hours.
ACGIH TLV (United States, 7/2023).
Ototoxicant. Notes: K
 TWA: 20 ppm 8 hours. Form:
OSHA PEL 1989 (United States, 3/1989).
 TWA: 100 ppm 8 hours.
 TWA: 435 mg/m³ 8 hours.
 STEL: 125 ppm 15 minutes.
 STEL: 545 mg/m³ 15 minutes.
NIOSH REL (United States, 10/2020).
 TWA: 100 ppm 10 hours.
 TWA: 435 mg/m³ 10 hours.
 STEL: 125 ppm 15 minutes.
 STEL: 545 mg/m³ 15 minutes.
OSHA PEL (United States, 5/2018).
 TWA: 100 ppm 8 hours.
 TWA: 435 mg/m³ 8 hours.
CAL OSHA PEL (United States, 5/2018).
 STEL: 130 mg/m³ 15 minutes.
 STEL: 30 ppm 15 minutes.
 TWA: 22 mg/m³ 8 hours.
 TWA: 5 ppm 8 hours.

Biological exposure indices

Ingredient name	Exposure indices
xylene	ACGIH BEI (United States, 7/2023) [xylenes (technical or commercial grades)] BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
ethylbenzene	ACGIH BEI (United States, 7/2023) BEI: 0.15 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
- The breakthrough time must be greater than the end use time of the product.
- The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
- Gloves should be replaced regularly and if there is any sign of damage to the glove material.
- Always ensure that gloves are free from defects and that they are stored and used correctly.
- The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
- Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
- Wear suitable gloves tested to ISO 374-1:2016.
- Recommended, gloves(breakthrough time) > 8 hours: Viton® (> 0.7 mm), nitrile rubber (> 0.75 mm), 4H/Silver Shield® (> 0.07 mm), Teflon (> 0.35 mm)
- Not recommended, gloves(breakthrough time) < 1 hour: PVC (> 0.5 mm)
- May be used, gloves(breakthrough time) 4 - 8 hours: neoprene (> 0.35 mm), butyl rubber (> 0.4 mm), polyvinyl alcohol (PVA) (> 0.3 mm)
- Body protection** : Use chemical-resistant protective suit / disposable overall.
- Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Grey, Red, aluminum
- Odor** : Characteristic.
- Odor threshold** : Not applicable.
- pH** : Not applicable.
- Melting point** : Not applicable.
- Boiling point** : Lowest known value: 108°C (226.4°F) (2-methylpropan-1-ol). Weighted average: 234.39°C (453.9°F)
- Flash point** : Closed cup: 34°C (93.2°F)

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
epoxy resin (MW ≤ 700)	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams 500 milligrams	-
	Skin - Mild irritant	Rabbit	-		
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams 8 hours 60 microliters	-
	Skin - Mild irritant	Rat	-		
Phenol, methylstyrenated	Skin - Mild irritant	Mammal - species unspecified	-	-	-
epoxy resin (MW 700-1200)	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-
benzyl alcohol	Eyes - Mild irritant	Mammal - species unspecified	-	-	-
2-methylpropan-1-ol	Eyes - Irritant	Mammal - species unspecified	-	-	-
	Skin - Mild irritant	Mammal - species unspecified	-	-	-

Sensitization

Product/ingredient name	Route of exposure	Species	Result
epoxy resin (MW ≤ 700)	skin	Mammal - species unspecified	Sensitizing
Phenol, methylstyrenated	skin	Mammal - species unspecified	Sensitizing
epoxy resin (MW 700-1200)	skin	Mammal - species unspecified	Sensitizing

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
epoxy resin (MW ≤ 700)	-	3	-
ethylbenzene	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
2-methylpropan-1-ol	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Name	Result
xylene ethylbenzene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
Inhalation : No known significant effects or critical hazards.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Route	ATE value
Oral	41000 mg/kg
Dermal	19555.56 mg/kg
Inhalation (vapors)	104.76 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
epoxy resin (MW ≤ 700)	Acute EC50 1.4 mg/l Acute LC50 3.1 mg/l	Daphnia Fish - pimephales promelas	48 hours 96 hours
xylene	Chronic NOEC 0.3 mg/l Acute LC50 8500 µg/l Marine water	Fish Crustaceans - Palaemonetes pugio	21 days 48 hours
2-methylpropan-1-ol	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
ethylbenzene	Chronic NOEC 4000 µg/l Fresh water Acute EC50 7700 µg/l Marine water Acute EC50 2.93 mg/l Acute LC50 4.2 mg/l	Daphnia - Daphnia magna Algae - Skeletonema costatum Daphnia Fish	21 days 96 hours 48 hours 96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
epoxy resin (MW ≤ 700)	-	-	Not readily
xylene	-	-	Readily
benzyl alcohol	-	-	Readily
ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
epoxy resin (MW ≤ 700)	2.64 to 3.78	31	low
xylene	3.12	8.1 to 25.9	low
Phenol, methylstyrenated	3.627	-	low
benzyl alcohol	0.87	<100	low
2-methylpropan-1-ol	1	-	low
ethylbenzene	3.6	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues.







Section 13. Disposal considerations

Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Xylene Isobutyl alcohol (I,T)	1330-20-7 78-83-1	Listed Listed	U239 U140

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	Paint	Paint	Paint	Paint	Paint	Paint
Transport hazard class(es)	3 	3 	3 	3 	3 	3 
Packing group	III	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.	No.

Additional information

- DOT Classification** : **Reportable quantity** 1777.8 lbs / 807.11 kg [126.09 gal / 477.3 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
- TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).
- Mexico Classification** : -
- ADR/RID** : Tunnel restriction code: (D/E)
Hazard identification number: 30
ADR/RID: Viscous substance. Not goods of class 3, ref. 2.2.3.1.5 (only applicable to receptacles < 450 litre capacity).
- IMDG** : Emergency schedules (EmS): F-E, S-E
Marine pollutant: No.
IMDG: Viscous substance. Transport in accordance with 2.3.2.5 of the IMDG Code (only applicable to receptacles < 450 litre capacity).
- IATA** : -
- Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- Transport in bulk according to IMO instruments** : Not available.

Section 15. Regulatory information

U.S. Federal regulations : Clean Water Act (CWA) 307: ethylbenzene
Clean Water Act (CWA) 311: xylene; ethylbenzene

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Ingredient name	CAS number	%
xylene	1330-20-7	5.625
ethylbenzene	100-41-4	1.875

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : FLAMMABLE LIQUIDS - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Composition/information on ingredients

Name	%	Classification
epoxy resin (MW ≤ 700)	≥10 - <25	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1B
xylene	≤10	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 ASPIRATION HAZARD - Category 1
Phenol, methylstyrenated	≤10	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1
epoxy resin (MW 700-1200)	≤5	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
benzyl alcohol	≤5	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 EYE IRRITATION - Category 2A
2-methylpropan-1-ol	<3	FLAMMABLE LIQUIDS - Category 3 SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
ethylbenzene	≤3	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY (inhalation) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

Section 15. Regulatory information

EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	xylene	1330-20-7	≤10
	ethylbenzene	100-41-4	≤3
Supplier notification	xylene	1330-20-7	≤10
	ethylbenzene	100-41-4	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : The following components are listed: limestone; XYLENE; BENZYL ALCOHOL; ISOBUTYL ALCOHOL; ETHYL BENZENE
- New York** : The following components are listed: Xylene mixed; Isobutanol; Ethylbenzene
- New Jersey** : The following components are listed: CALCIUM CARBONATE; XYLENES; ISOBUTYL ALCOHOL; ETHYL BENZENE
- Pennsylvania** : The following components are listed: limestone; BENZENE, DIMETHYL-; BENZENEMETHANOL; 1-PROPANOL, 2-METHYL-; BENZENE, ETHYL-

California Prop. 65

WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
ethylbenzene	Yes.	No.	Yes.	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

- Australia** : Not determined.
- Canada** : Not determined.
- China** : Not determined.
- Europe** : Not determined.
- Japan** : Not determined.
- Malaysia** : Not determined.
- New Zealand** : Not determined.
- Philippines** : Not determined.
- Republic of Korea** : Not determined.

Section 15. Regulatory information

Taiwan : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

History

Date of printing : 18.07.2024

Date of issue/Date of revision : 18.07.2024

Date of previous issue : 28.05.2024

Version : 1.06

Key to abbreviations

: ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

➤ Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.