## SAFETY DATA SHEET



## Jota Armour Std Comp B

## Section 1. Identification

GHS product identifier : Jota Armour Std Comp B

Product code : 463

Other means of identification

: Not available.

Product type : Liquid.
Product description : Hardener.

## Relevant identified uses of the substance or mixture and uses advised against

Use in coatings - Industrial use
Use in coatings - Professional use

Supplier's details : 佐敦涂料(张家港)有限公司

江苏省张家港保税区扬子江化学工业园长江路15号 215634

电话: +86 512 58937988 传真: +86 512 58937986

Jotun Coatings (Zhangjiagang) Co. Ltd

No.15 Changjiang Road Jiangsu Yangtze River International Chemical Industry Park,

Zhangjiagang Free Trade Zone, Jiangsu Province 215634

Tel: +86 512 58937988 Fax: +86 512 58937986

Jotun Paints (Malaysia) Sdn Bhd, Lot 7 Persiaran Perusahaan, Section 23

40300 SHAH ALAM, Selangor Darul Ehsan

Malaysia

Tel: +603 51235500 Fax: +603 51235599

SDSJotun@jotun.com

Emergency telephone number (with hours of

operation)

: Jotun Coatings (Taiwan) Ltd. Co. Tel: +886 2 87705061

## Section 2. Hazards identification

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 5
SKIN CORROSION/IRRITATION - Category 1A
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
SKIN SENSITISATION - Category 1

**GHS label elements** 

Hazard pictograms :





Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 1/11

## Section 2. Hazards identification

Signal word

: Danger.

**Hazard statements** 

: H303 - May be harmful if swallowed.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

#### **Precautionary statements**

**Prevention** 

: P280 - Wear protective gloves, protective clothing and eye or face protection.

P261 - Avoid breathing vapour.

Response

: P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor. P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER

or doctor.

P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

**Storage** 

: Not applicable.

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not : None known.

result in classification

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

Not available.

Product name	% (w/w)	CAS number	Type
penzyl alcohol	≥10 - ≤25	100-51-6	[1]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	≤14	2855-13-2	[1]
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	≤7.3	25513-64-8	[1]
<b>→</b> □ 44		a . a H +++	Mr. mod
产品名称	% (w/w)	CAS号码	类型
<b> </b>	<b>% (w/w)</b> ≥10 - ≤25	CAS号码 100-51-6	<b>类型</b> [1]
	` '		<u> </u>

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### **Type**

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 25.11.2024 : 26.06.2024 Version: 1.08 2/11 Date of previous issue

## Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Most important symptoms/effects, acute and delayed

## Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Ingestion** : May be harmful if swallowed.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments**: No specific treatment.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 3/11

## Section 4. First aid measures

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

# Specific hazards arising from the chemical

Hazardous thermal decomposition products

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides carbonyl halides

# Special protective actions for fire-fighters

Special protective equipment for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### **Environmental precautions**

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 4/11

## Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

None.

## **Biological exposure indices**

No exposure indices known.

## Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

## **Individual protection measures**

## **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

#### **Hand protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Wear suitable gloves tested to ISO 374-1:2016.

Recommended, gloves(breakthrough time) > 8 hours: 4H/Silver Shield® (> 0.07 mm), butyl rubber (> 0.4 mm), fluor rubber (> 0.35 mm), Viton® (> 0.7 mm) May be used, gloves(breakthrough time) 4 - 8 hours: nitrile rubber (> 0.75 mm), PVC (> 0.5 mm)

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 5/11

## Section 8. Exposure controls/personal protection

For right choice of glove materials, with focus on chemical resistance and time of penetration, seek advice by the supplier of chemical resistant gloves.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Eye protection** 

: Safety eyewear complying to ISO 16321-1:2022 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

**Body protection** 

: Use chemical-resistant protective suit / disposable overall.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

## **Appearance**

Physical state
Colour
Colour
Colour
Colour
Colour
Colour
Colour
Colourless.
Characteristic.
Not available.
Not applicable.
Melting point/freezing point
Colourless.
Not available.
Not applicable.
Not applicable.
Not available.
point, and boiling range

Flash point : Closed cup: 112°C (233.6°F)

Flammability : Not available.

Lower and upper explosion : Not applicable.

limit/flammability limit

Vapour pressure

	Vapour Pressure at 20°C		Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
benzyl alcohol	0.05	0.0067				
2,2,4(or 2,4,4)-trimethylhexane- 1,6-diamine	0.03	0.004	OECD 104			
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	0.01178	0.0016	OECD 104			

**Relative vapour density** : Not available. **Density** : 1.03 g/cm³

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 6/11

# Section 9. Physical and chemical properties and safety characteristics

Solubility(ies)

Media	Result
cold water	Not soluble
hot water	Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
3-aminomethyl-3,5,5-trimethylcyclohexylamine	380	716	
benzyl alcohol	436	816.8	

**Decomposition temperature**: Not available.

Viscosity : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)

**Particle characteristics** 

Median particle size : Not applicable.

## Section 10. Stability and reactivity

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **Section 11. Toxicological information**

## Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol 3-aminomethyl- 3,5,5-trimethylcyclohexylamine	LD50 Oral LD50 Oral		1230 mg/kg 1030 mg/kg	-

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Eyes - Mild irritant	Mammal -	-	-	-
		unspecified			

#### **Sensitisation**

•	Route of exposure	Species	Result
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	skin	Mammal - species unspecified	Sensitising
2,2,4(or 2,4,4)- trimethylhexane-1,6-diamine	skin	Mammal - species unspecified	Sensitising

## **Mutagenicity**

## Section 11. Toxicological information

Not available

## **Carcinogenicity**

Not available.

## **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

## Specific target organ toxicity (single exposure)

Not available.

## Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on likely routes

of exposure

: Not available.

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes severe burns. May cause an allergic skin reaction.

**Ingestion**: May be harmful if swallowed.

## Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

## Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 8/11

## Section 11. Toxicological information

Mutagenicity : No known significant effects or critical hazards.Reproductive toxicity : No known significant effects or critical hazards.

## **Numerical measures of toxicity**

## **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(0)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Jota Armour Std Comp B	2112.0	N/A	N/A	45.3	N/A
benzyl alcohol	1230	N/A	N/A	11	N/A
3-aminomethyl-3,5,5-trimethylcyclohexylamine	1030	N/A	N/A	N/A	N/A
2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	500	N/A	N/A	N/A	N/A

## Section 12. Ecological information

## **Toxicity**

Product/ingredient name	Result	Species	Exposure
3-aminomethyl- 3,5,5-trimethylcyclohexylamine	Acute EC50 388 mg/l	Crustaceans	48 hours
	Acute EC50 23 mg/l	Daphnia	48 hours
	Acute LC50 110 mg/l	Fish	96 hours
2,2,4(or 2,4,4)-	Acute EC50 43.5 mg/l	Aquatic plants	72 hours
trimethylhexane-1,6-diamine			
•	Acute EC50 89 mg/l	Micro-organism	17 hours
	Chronic NOEC 16 mg/l	Algae	72 hours
	Chronic NOEC 1.02 mg/l	Daphnia	21 days
	Chronic NOEC 10.9 mg/l	Fish	34 days

## Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
benzyl alcohol 3-aminomethyl-	-		Readily Not readily
3,5,5-trimethylcyclohexylamine 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine	-	-	Not readily

## **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	<100	low
3-aminomethyl-	0.99	-	low
3,5,5-trimethylcyclohexylamine			
2,2,4(or 2,4,4)-	-0.3	-	low
trimethylhexane-1,6-diamine			

## **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 9/11

## Section 13. Disposal considerations

## **Disposal methods**

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

	UN	IMDG	IATA
UN number	UN2735	UN2735	UN2735
UN proper shipping name	Polyamines, liquid, corrosive, n.o.s. (2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)	Polyamines, liquid, corrosive, n.o.s. (2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)	Polyamines, liquid, corrosive, n.o.s. (2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine)
Transport hazard class(es)	8	8	8
Packing group	III	III	III
Environmental hazards	No.	No.	No.

**Additional information** 

ADR/RID : Tunnel restriction code: (E)

Hazard identification number: 80

**IMDG** : **Emergency schedules** F-A, S-B

Segregation Group: 18 - Alkalis

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

## Section 15. Regulatory information

**TCCSCA List of toxic chemicals** 

Not applicable.

**TCCSCA List of concerned chemicals** 

Not applicable.

Priority management chemicals, Article 2

CMR chemical substances, category 1 (Article 2.2 (I)) : Applicable

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Date of issue/Date of revision : 25.11.2024 : 26.06.2024 Version : 1.08 10/11 Date of previous issue

## Section 15. Regulatory information

## **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

## Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 5	Calculation method
SKIN CORROSION/IRRITATION - Category 1A	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	Calculation method
SKIN SENSITISATION - Category 1	Calculation method

References : Not available.

Organisation that prepared : Jotun AS, Norway +47 33 45 70 00

**History** 

Date of printing : 25.11.2024

Date of previous issue : 26.06.2024

Version : 1.08

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.

Date of issue/Date of revision : 25.11.2024 Date of previous issue : 26.06.2024 Version : 1.08 11/11