

## Majestic Design Stucco Antica

---

### Product description

#### Type

This product is a high quality waterborne paint.

#### Features and benefits

It is ideal to create an elegant and antique finish. It comes in a beautiful selection of colours which will help you create the perfect look.

#### Recommended use

It is recommended for hotels, restaurants, villas and all other prestigious interiors.

#### Substrate

Is a topcoat which is specially formulated for interior use on plaster, concrete, gypsum board, MDF, plywood etc.

---

### Product data

<b>Packaging size</b>	1L , 4L and 10L
<b>Colours</b>	Refer to Majestic Design Book.
<b>Gloss level</b>	Matt
<b>Solids by volume</b>	50 ± 2 volume%
<b>Specific gravity</b>	

---

### Application data

#### Remarks

Stir well before use. Handle with care.

#### Application equipment / methods

Trowel, pallet knife or other suitable dispenser.

#### Spreading rate per coat

Depending on thickness applied. In a practice, the need of paint is 0.7 to 1 Kg/Sq.m/Coat.

#### Thinner

Water

#### Dilution

The paint is ready to use after proper stirring. If thinning is required, water may be added up to a maximum of 3%.

#### Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

### Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly. The figures given in the table are typical with:

Good ventilation (Outdoor exposure or free circulation of air)

Typical film thickness

One coat on top of inert substrate

The given data must be considered as guidelines only. The actual drying time and time before recoating may be shorter or longer, depending on the ambient temperature, film thickness, ventilation, humidity, underlying paint system, requirement for early handling and mechanical strength etc.

1. Recommended data given is, for recoating with the same generic type of paint.

2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.

3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

#### The drying time is measured by stated values:

**Relative Humidity (RH) 50 %**

**Substrate temperature** 23 °C

<b>Surface (touch) dry</b>	1 h
<b>Hard dry</b>	5 h
<b>Dry to over coat, minimum</b>	1 h

## Directions for use

### Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

### Recommended paint system

#### Primer

Majestic Primer (C) : 1 coat

#### Topcoat

Majestic Matt (C) : 2 coats

Majestic Design Stucco Antica : 4 Coats, 2 coats with smooth finish and 2 coats with desired design.

### Other paint systems

Other systems may be specified, depending on area of use.

### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

---

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.