

SeaRenew

Product description

This is a patented cleaning solution designed to remove discoloration visible upon extended outfitting periods in connection with new building projects. It is thoroughly tested and evaluated with Jotun's antifouling coatings.

Typical use

Recommended for use where Jotun's biocidal antifouling has discoloured and there is a desire to renew the appearance.

For necessary application guidelines, please refer to the Application Guide (AG).

Colours

clear

Product data

Property	Test/Standard	Description
Solids by volume	ISO 3233	29 ± 2 %
Flash point	ISO 3679 Method 1	100 °C
Density	calculated	1.2 kg/l

The provided data is typical for factory produced products, subject to slight variation depending on colour.

Application

Application methods

The product can be applied by

Spray: Use airless spray.

Product mixing

Single pack

Add one liter of SeaRenew to an empty 20 liter plastic bucket. Add 19 liter of fresh water and stir manually until a homogeneous solution has been obtained.

Thinner/Cleaning solvent

Thinner: Fresh water

Guiding data for airless spray

Usually the best spray fan is obtained in the absence of a tip.
Refer to the Application Guide (AG) for additional information or contact your nearest Jotun office.

Packaging (typical)

	Volume (litres)	Size of containers (litres)
SeaRenew	20	20

The solution is usually supplied in 20 liter plastic buckets, with a 1 liter plastic measuring cup to dosage the appropriate amount while mixing.

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Protect from freezing at all times during storage and transport.

Shelf life at 23 °C

SeaRenew 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Caution

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product. Any suggested deviation to suit the site conditions shall be forwarded to the responsible Jotun representative for approval before commencing the work.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Colour variation

When applicable, products primarily meant for use as primers or antifoulings may have slight colour variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Colour and gloss retention on topcoats/finish coats may vary depending on type of colour, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.
