

Rehabilit Perfect

Product description

Type

This product is an acrylic waterproofing coating with great resistance to the elements, specially indicated for the protection of facades. Thanks to its anti-reflective formula and its high hiding power, it is ideal to conceal small imperfections in all kinds of exterior masonry surfaces.

Features and benefits

Extra matt finish. Extraordinary coverage. Conceals imperfections of the surface. High resistance to exteriors. High resistance to UV rays. Breathable. Very good adhesion. Easy application. It does not splash. Prevents mold and mildew formation in the paint film.

Recommended use

Easy application and good hiding power, outdoor and indoor (houses, warehouses, parking lots, works), on all types of surfaces such as drywall, plaster, cement, concrete, walls etc.

Product data

Packaging size	4 L and 15 L
Colours	White and Colours available in Jotun Multicolor system.
Solids by volume	49 ± 2 volume%
Specific gravity	1.55 Theoretical

Application data

The product can be applied by

Brush : Recommended.

Roller : Recommended.

Spray : Airless spray may be used.

Guiding data for airless spray

Nozzle tip	0.021–0.027"
Spray angle degrees	65–80°
Pressure at nozzle	140 - 190 kg/cm ² (2100 psi)

Film thickness per coat

Typical recommended range

Dry film thickness	25 - 40 μm
Wet film thickness	70 - 115 μm

Film thickness will vary and is calculated as average.

Theoretical spreading rate	10 - 7 m ² /l
----------------------------	--------------------------

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly. The figures given in the table are typical with:

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Substrate temperature	10 °C	23 °C
Surface (touch) dry	1 h	0.5 h
Hard dry	60 h	24 h
Dry to over coat, minimum	10 h	6 h

Directions for use

Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

Recommended paint system

Primer

Jotashield Penetrating Primer Blanco : 1 Coat

Topcoat

Rehabilit Perfect : 2 Coats

Remarks

Other systems may be specified, depending on area of use.

Contents of packaging with different batch numbers must be mixed together before use.

Please refer to the Decorative Sales Department for technical advice.

Shelf life at 23 °C

Rehabilit Perfect 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.