

## Majestic Glaze

---

### Product description

#### Type

This paint is durable interior water-based glaze based on a special modified acrylic binder with semi-transparent colour and sheen finish.

#### Recommended use

Specially designed for creating interior decorative effects such as sponging, colour washing, stenciling and dragging.

---

### Product data

**Packaging size** Packing may vary from country to country according to local requirements.  
**Solids** 35 ± 2 volume%

---

### Application data

#### Remarks

Handle with care. Stir well before use.

#### Application methods

Brush or roller.

#### Conditions during application

Apply at room temperature not lower than 15 degree C.

#### Recommended film thickness per coat

Film thickness will vary and is calculated as average.

#### Spreading rate per coat

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

#### Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly. The figures given in the table are typical with:

Good ventilation (Outdoor exposure or free circulation of air)

Typical film thickness

One coat on top of inert substrate

The given data must be considered as guidelines only. The actual drying time and time before recoating may be shorter or longer, depending on the ambient temperature, film thickness, ventilation, humidity, underlying paint system, requirement for early handling and mechanical strength etc.

1. Recommended data given is, for recoating with the same generic type of paint.
  2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
  3. The surface should be dry and free from any contamination prior to application of the subsequent coat.
-

<b>Relative Humidity (RH)</b>	50 %	50 %
<b>Substrate temperature</b>	23 °C	40 °C
<b>Surface (touch) dry</b>	90 min	20 min
<b>Hard dry</b>	8 h	3 h

## Directions for use

### Surface preparation

The substrate ( final coat of Majestic ) must be sound, clean, free from dust, oil, grease and laitance etc. It must be dry for at least 24 hours before applying Majestic Glaze.

### Recommended paint system

#### Primer

Jotasealer 07 or Cito Primer 09 White : 1 Coat(s)

#### Topcoat

Majestic : 2 Coat(s)

Majestic Glaze : 1 Coat(s)

### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health- and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.