

## Fenomastic Macun

### Product description

#### Type

This product is a water based interior putty which does not require a primer application and offers excellent finish by filling the gaps and pores.

#### Features and benefits

It ensures a very smooth and even finish with faster application process which saves time and money. Ready to use. With its high filling feature, it creates a smooth surface. It is easy to apply and has good spreading property. It requires light sanding, which results in a very small amount of dust. It is a "2in1" product - putty and primer together. Interior topcoat can be applied after the putty application without primer. It is fast-drying product which saves time and application cost. Excellent adhesion to substrate provides a high performance paint film.

#### Recommended use

Ideal for interior wall surfaces.

#### Substrate

Cement plaster, concrete, block work, gypsum board etc.

### Product data

<b>Packaging size</b>	4 kg and 25 kg
<b>Colours</b>	White
<b>Solids by volume</b>	50 ± 2 volume%
<b>Specific gravity</b>	1.75 Theoretical
<b>VOC</b>	11 g/l ISO 11890 EU

### Application data

#### The product can be applied by

Putty knife : Recommended.

Trowel : Recommended.

Spray : Use airless spray or conventional spray.

#### Cleaning of painting tools

Water

### Film thickness per coat

#### Typical recommended range

Dry film thickness                      65 - 110 µm  
Wet film thickness                      130 - 220 µm  
Film thickness will vary and are calculated as an average.

Spreading rate per coat (m<sup>2</sup>/kg) : 4.4 - 2.6

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

### Dilution

The product is ready to use and must not be diluted.

### Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

### Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

#### The drying time is measured by stated values:

##### Relative Humidity (RH) 50 %

Substrate temperature	10 °C	23 °C	40 °C
Surface (touch) dry	1 - 2 h	40 - 50 min	20 - 30 min
Hard dry	2 - 4 h	1 - 2 h	30 - 40 min
Dry to over coat, minimum	2 - 4 h	1 - 2 h	30 - 40 min

## Directions for use

### Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

### Recommended paint system

#### Filler

Fenomastic Macun : 2 Coats

#### Topcoat

Fenomastic series : 2 Coats

## Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.