

Majestic Beauty & Resist

Product description

Type

This product is a superior quality emulsion paint, designed for beautiful interior surfaces. Based on acrylic emulsion.

Features and benefits

Majestic Beauty & Resist can be used for decorating walls and ceilings with an exclusive matt finish, resistant and super-washable. Its innovative formulation gives it high resistance to stains and scratches. Exceptional washability and resistance to wet rubbing on the most common household stains. Class 1 according to UNE-EN ISO 11998. Durable and stable colors over time. Excellent hiding power. It does not smell. It does not splatter. The product reaches its maximum resistance after 3 weeks of drying.

Recommended use

Specially formulated top coat for indoor use and recommended for Hotels, Restaurants, Villas and all other prestigious interiors.

Substrate

Cement plaster, concrete, block work, rendered surfaces, plasterboard, etc.

Product data

Packaging size	0.9 L, 2.5 L, 4 L, 10 L and 15 L
Colours	As per colour card and available in Jotun Multicolor tinting system (Interior range).
Solids by volume	40 ± 2 volume% Theoretical
Specific gravity	1.17
VOC	5 g/l ISO 11890 EU

Application data

The product can be applied by

Roller : Recommended.

Brush : Recommended to paint corners and edges.

Spray : Use airless spray or conventional spray.

Guiding data for airless spray

Nozzle tip	0.021-0.027"
Spray angle degrees	65-85°
Pressure at nozzle	150 Kg/cm ² (2100 psi)

Film thickness per coat

Typical recommended range

Dry film thickness 35 - 50 μm

Wet film thickness 85 - 125 μm

Film thickness will vary and is calculated as average.

Theoretical spreading rate 12 - 8.4 m^2/l

Spreading rate depends on film thickness applied, type of texture, surface porosity, imperfections, temperature, wastage during painting etc.

Maximum spread rate per coat is obtained at minimum dry film thickness and vice versa.

Dilution

Ready to use.

Conditions during application

The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. Good ventilation is usually required in confined areas to ensure proper drying.

Drying times

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly. The figures given in the table are typical with:

1. Recommended data given is, for recoating with the same generic type of paint.
2. In case of multi-coat application, drying times will be influenced by the number and sequence and by the total thickness of previous coats applied.
3. The surface should be dry and free from any contamination prior to application of the subsequent coat.

The drying time is measured by stated values:

Relative Humidity (RH) 50 %

Substrate temperature	10 °C	23 °C
Surface (touch) dry	1 h	0.5 h
Hard dry	12 h	6 h
Dry to over coat, minimum	12 h	6 h

Directions for use

Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

Recommended paint system

Primer

Rehabilit Fondo Penetrante : 1 Coat (1 part diluted with 4 parts of water)

Topcoat

Majestic Beauty & Resist : 2 Coats

Remarks

Other systems may be specified, depending on area of use.

Contents of packaging with different batch numbers must be mixed together before use.

Please refer to the Decorative Sales Department for technical advice.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care. Storage temperature should be between 10 and 30 °C.

Shelf life at 23 °C

Majestic Beauty & Resist 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Tests

The resistance of Majestic Beauty & Resist paint has been tested by an independent center for applied research and technological development according to UNE-EN ISO 11998. Majestic Beauty & Resist paint has been compared to the benchmark interior matt and superwashable paints on the market. Majestic Beauty & Resist has been certified as superior on the most common household stains. Consult the certificate on www.jotun.es or contact your closest Jotun dealer.

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.